

80MM

OCPP-80

8

100M

256KB NV Logo256kb

POS/JPOS

100KM

	ESC/POS
	576 5 1 2
	=72mm
	U SB / UL /U +BT / U+WIFI
	200 /U 2 60 / (UL)
	80mm
	0.06~0.08mm
	Ø 83
	256kbytes
	256kbytes
	A12*24B9*17
	GB18030,BIG5 24x24
	PC347(),PC850(),PC860(),PC863(),PC865(), , , , ,WPC1252,PC866(Cyrillic#2), PC852(Latin2), PC858,IranII,Latvian,Arabic,PT151(1251)
	UPC-A/UPC-E/JAN13 EAN13 /JAN8 EAN /CODE39/ITF/CODABAR/CODE93/CODE128
	QRUSBURQR
	100
	100V-240V 50/60HZ
	24V/2.5A
	0°C~45°C10%~80%RH
	-10°C-60°C10%~90%RH
	1 80 ()x14 2 ()x13 6 ()mm
	1.14
	1. 8
	Windows XP /Vista/ Win7/Win8 /Win10/Win 2000/Win CE/OPOS/JPOS
	iOS











Selftest

Firmware Version : 1.32700
Print Speed : 280mm/s
Command mode : EPSON ESC/POS
Firmware modify : 2009/02/12
Cutter enable : No
Buzzer enable : Yes
Black mark mode : No
Density Level : 5 (Max=6)
Character per line : 48/64
Default ASCII FONT : FONT1
Default code page : Page0
Default W download : Yes
Image W download : Yes
Blackmark SENS L : 8, 12
Blackmark SENS H : 8, 12
Arista Core 000
Arista Core 000
Arista Core 000

It's More Than A Printer










Thermal Printer



Together we quest for the best

