

200 80

OCPP-80T

□□□

□□□□□□□□ □□ □□□□□

□□□□□□□□□□

100M□□□□□□□□□□□□

256kb NV Logo □□□ 256kb □□□□□□□

□□OPOS/JPOS □□□

100KM□□□□□□

□□□□□

□□□□	□□□
□□□	576□/□□5 1 2□/□
□□□□	□□=72mm
□□□□	□□□□□
□□□□	200 □□/□ □□□ 2 6 0 □□/□ (UL)
□□□□	80mm
□□□□	0.06~0.08mm
□□	□□□□□ Ø 83 □□
□□	□□□□□□□□□□
□□□□□□	256kbytes
NV□□	256kbytes
□□□□	□□A□12*24□□□□□□□□B□9*17
□□□□	GB18030,BIG5 24x24dots
□□/□□	□□
□□□□□□□□	PC347(□□□□),□□□,PC850(□□□□),PC860(□□□□),PC863(□□□□-□□),PC865(□□□),□□,□□□□,□□□□□□,□□,□□, WPC1252,PC866(□□□□#2), PC852(□□□2), PC858□Iran□□□□□□□□□□□□□□PT151(1251) □□
□□	UPC-A/UPC-E/JAN13 □ EAN13 □ /JAN8 □ EAN8 □ /CODE39/ITF/CODABAR/CODE93/CODE128
□□	□□□ (S □□ USB □ UR □□□□ □ □□□□□□□)
□□□□□□	100 □□
□□□□	□□
□□□□	□□□□□□□□□□□□□□□□□□□□
□□	□□ 100V-240V 50/60HZ
□□	□□ 24V/2.5A
□□□□	0°C~45°C, 10%~80%RH
□□□□	-10°C-60°C,10%~90%RH
□□	□□□□□□□□□□□□□□□□□□□□CD□□□□□□□□□□ □□□□□□□□□□
□□	1.14□□
□□□	1. 8 □□
□□	Windows XP/Vista/Win7/Win8/Win10/Win 2000/Win CE/OPOS/JPOS
SDK	□□□iOS













