

80MM 80MM

OCPP-80

80MM

80MM

80MM

80MM

100M

256KB NV Logo 256kb

POS/JPOS

100KM

80MM

80MM	80MM
80	ESC/POS
80	576 5 1 2
80	=72mm
80	
80	U SB / UL / U +BT / U+WIFI
80	200 U 2 60 / (UL)
80	80mm
80	0.06~0.08mm
80	Ø 83
80	
80	256kbytes
80	256kbytes
80	A12*24 B9*17
80	GB18030,BIG5 24x24
80	
80	PC347(),PC850(),PC860(),PC863(),PC865(), , , , ,WPC1252,PC866(Cyrillic#2), PC852(Latin2), PC858,IranII,Latvian,Arabic,PT151(1251)
80	UPC-A/UPC-E/JAN13 EAN13 /JAN8 EAN /CODE39/ITF/CODABAR/CODE93/CODE128
80	QR USB UR QR
80	100
80	
80	
80	
80	100V-240V 50/60HZ
80	24V/2.5A
80	0°C~45°C 10%~80%RH
80	-10°C-60°C 10%~90%RH
80	
80	
80	1 80 ()x14 2 ()x13 6 ()mm
80	1.14
80	1. 8
80	Windows XP /Vista/ Win7/Win8 /Win10/Win 2000/Win CE/OPOS/JPOS
80	IOS









Selftest

Firmware version : 1.3206a
Print Speed : 280mm/s
Command mode : EPSON (ESC/POS)
Firmware mode : 2000/02/12
Cutter enable : No
Feeder enable : No
Black mark mode : 5 (Max=6)
Density Level :
Character per line : 48/84
Default ASCII FONT : FONT1
Default code page : Page0
Default W/Load : Yes
Stackmark SEAS L : 8, 12
Align Load : 000
Align Load : 000
Align Load : 000









Thermal Printer



Together we quest for the best



ACOM Thermal Receipt Printer
Model: DCFP-801 Cutter: YES
Interface: USB/LAN Paper Width: 80mm
Power Input: 24V/2.5A Print Speed: 360mm/sec
Cash Drawer: 34411A
OCPP9072232400007
CE FCC Made in China

Thermal Printer



Together we quest for the best

