

80 毫米 MM

OCPP-80

- 1. 8i
- 2. 256kb NV 256kb
- 3. 100M
- 4. 256kb NV 256kb
- 5. C POS /JPOS
- 6. 100KM

	ESC/POS
	576/5 1 2
	=72mm
	U SB / UL /U BT / UWIFI
	200 / 2 6 0 /UL
	80
	0.06~0.08mm
	Ø 83
	256KB
	256KB
	A12*24B9*17
	GB18030,BIG5 24x24
	PC347PC850PC860PC863PC865WPC1252PC866#2
	,PC852), PC858IPT151(1251)
	UPC-A/UPC-E/JAN13 EAN13 /JAN8 EAN8 /CODE39/ITF/CODABAR/CODE93/CODE128
	(S USB UR
	100
	100V-240V 50/60HZ
	24V/2.5A
	0°C45°C10%80%RH
	-10°C-60°C,10%~90%RH
	1 80 (D)x14 2 x13 6
	1.14
	1. 8
	Windows XP /Vista/Win7/Win8/Win10/Win 2000/Win CE/OPOS/JPOS











Selftest

Firmware Version : 1.32700
Print Speed : 280mm/s
Command mode : EPSON ESC/POS
Firmware modify : 2009/02/12
Cutter enable : No
Beeper enable : Yes
Black mark mode : No
Density Level : 5 (Max=6)
Character per line : 48/64
Default ASCII FONT : FONT1
Default code page : Page0
Default W download : Yes
Image W download : Yes
Blackmark SENS L : 8, 12
Blackmark SENS H : 8, 12
Arista Core 000
Arista Core 000
Arista Core 000










Thermal Printer



Together we quest for the best

