

80 80MM

OCPP-80T

□□□

1. 8000i
2. □□□□□□ □□ □□□□
3. □□□□□□□□
4. 100M□□□□□□□□□□
5. 256kb NV Logo □□ 256kb □□□□□□
6. C □ O □□POS /JPOS □□
7. 100KM□□□□□□

□□□□

□□□□	□□□
□□	E□□C□/POS
□□□	576□/□□5 1 2□/□
□□□□	□□=72mm
□□□□	□□□□□
□□	ü □□ / üL /ü BT / üWIFI
□□□□	200 □□/□ □□□ 2 6 0 □□/□ (UL)
□□□□	80mm
□□□□	0.06~0.08mm
□□	□□□□ Ø 83 □□
□□	□□□□□□□□□□
□□□□□	256kbytes
NV□□	256kbytes
□□□□	□□A□12*24□□□□□□□□B□9*17
□□□	GB18030,BIG5 24x24dots
□□/□□	□□
□□□□□□□□	PC347(□□□□),□□□,PC850(□□□),PC860(□□□□),PC863(□□□□□□),PC865(□□),□□,□□□,□□□□,□□,□□, WPC1252,PC866(□□□□□#2), PC852(□□□2), PC858□Iran□□□□□□□□□□□□□□PT151(1251) □□
□□	UPC-A/UPC-E/JAN13 □ EAN13 □ /JAN8 □ EAN8 □ /CODE39/ITF/CODABAR/CODE93/CODE128
□□	□□□ (S □□ USB □ UR □□□□ □ □□□□□□□)
□□□□ □□	100 □□
□□ □□	□□
□□□□	□□ □
□□□□	□□□□□□□□□□□□□□□□□□□□
□□	□□ 100V-240V 50/60HZ
□□	□□ 24V/2.5A
□□□□	0°C~45°C, 10%~80%RH
□□□□	-10°C-60°C,10%~90%RH
□□	□□□□□□□□□□□□□□□□□□□□CD□□□□□□□□□□□□
□□	1 80 (D)x14 2 (□)x13 6 □□
□□	1.14□□
□□□	1. 8 □□
□□	Windows XP /Vista/ Win7/Win8 /Win10/Win 2000/Win CE/OPOS/JPOS
SDK	□□□□IOS











Selftest

Firmware version : 1.3204a
Print Speed : 280mm/s
Command mode : EPSON ESC/P (P01)
Firmware mode : 2000/02/12
Cutter enable : No
Feeder enable : No
Black mark mode : 5 (Max=6)
Density Level :
Character set / line : 48/84
Default ASCII font : FONT1
Default code page : Page0
Image W/ load lock : Yes
Stackmark SEAS L : 8, 12
Align Load : 000
Align Load : 000
Align Load : 000
Align Load : 000









Thermal Printer



Together we quest for the best



ACOM Thermal Receipt Printer
Model: DCFP-801 Cutter: YES
Interface: USB/LAN Paper Width: 80mm
Power Input: 24V/2.5A Print Speed: 360mm/sec
Cash Drawer: 84011A
OCPP9072232400007
CE FCC Made in China

Thermal Printer



Together we quest for the best

