

□□□□□80□□□□□□□□□□

OCPP -80V

111

QR-PDF417

□□□□□□□□□□;

200mm / s□□□□;

□□□□□□□□;

```
100□□□□□□□□□□□□□□;
```

```
256KB NV128KB;
```

```
__IAP__;
```

□□OPOS / JPOS□□□□;

100□□□□□□□□

□□□□□

□□□□	□□□□
□□	ESC / POS
□□□	576dots / line□512dots / line
□□□□	max = 72mm.
□□□□	□□□□□□
□□	USB□USB + LAN□URL□BT WiFi□□□□□
□□□□	200mm / s
□□□□	80□□
□□□□	0.06□0.08mm.
□□□□	□□83□□
□□	□□□□□□□□□□
□□□□□□	256kbytes.
NV Flash.	128kbytes□□□USB 64KB□
□□□□	□□A□12 * 24□□□□□□□□B□9 * 17
□□	GB18030□Big5 24x24dots
□□/□□	□□
□□□□□□□□	PC347□□□□□□□□□□□□PC850□□□□□□□□PC860□□□□□□□□PC863□□□□□□□□□□PC865□□□□□□□□□□□□□□□□WPC1252□PC866□□□□□□□□2□□ pc852□□□□□2□□□ PC858□□□□□□□□□□□□□□PT151□1251□□□□
1D	UPC-A / UPC-E / JAN13□EAN13□/ JAN8□EAN8□/ CODE39 / ITF / CODABAR / CODE93 / CODE128
2D.	QR□□PDF417□□□USB□□□□□□□□
□□□□□□	100□□.
□□□□	□□
□□□□	□□□□
□□□	□□□□□□□□□□□□□□□□□□□□
□□	AC 100V-240V 50 / 60Hz
□□	DC 24V / 2.5A
□□□□	0°C□45°C□10□□80□RH
□□□□	-10°C-60°C□10□□90□RH
□□	□□□□□□□□□□□□□□□□CD□□□□□□□□□□ □□□□□□□□□□
□□	190.16□d□x140□w□x134.64□h□mm
□□	1□□
□□	Windows XP / Vista / Win7 / Win8 / Win10 / Win 2000 / Win CE / O POS / J POS
SDK.	Android□iOS.









OCP-80V







OCPP-80V





OCPP-80V

