

□□□□□□80□□□□□□

□□□□OCPP -80V□



□□□□

□□□□	□□□
□□	ESC / POS
□□□	576□/□512dots / line
□□□□	max = 72mm.
□□□□	□□□□
□□	USB□USB + LAN□URL□BT WiFi□□□□□
□□□□	200mm / s
□□□□	80□□
□□□□	0.06□0.08mm.
□□DIA	□□□□ □83□□
□□	□□□□□□□□□□

RAM	256kbytes.
NV Flash.	128kbytes USB 64KB
Screen	A 12 * 24 B 9 * 17
Font	GB18030 Big5 24x24dots
OS	
Supported PC	PC347 PC850 PC860 PC863 PC865 WPC1252 PC866 2 PC852 PC858 PT151 1251
1D	UPC-A / UPC-E / JAN13 EAN13 / JAN8 EAN8 / CODE39 / ITF / CODABAR / CODE93 / CODE128
2D	QR PDF417 USB
Resolution	100.
Power	
Input	
Output	
Power	AC 100V-240V 50 / 60Hz
Power	DC 24V / 2.5A
Temperature	0°C 45°C 10% 80% RH
Temperature	-10°C -60°C 10% 90% RH
Barcode	CD
Dimensions	190.16 [d] x 140 [w] x 134.64 [h] mm
Weight	1
OS	Windows XP / Vista / Win7 / Win8 / Win10 / Win 2000 / Win CE / O POS / J POS
SDK.	Android iOS.