

80 80 80 80 80 80

(M/N: OCPP-80V)

80 80

1. 80 80,PDF417 80 80
2. 80 80 80 80
3. 100M 80 80 80 80 80
4. 256KB NV Logo 80 128KB 80 80 80
5. 80 80 P 80 80
6. 80 80 80

80

80	OCPP-80V
80	80mm 80 80 80 80 80 80
80	80
80	U 80 B 80 USB LAN 80 URL 80 BT WIFI 80 80 80
80	I 80 80 100V-240V,50-60Hz , 80 80 80 24V / 2.5 A
80	80 24V/1A
80 80	80 80 80 80 80 80 80 80 Max.20K
80 80	100
80 80	100
80	80 80
80	80 80 80 80 80 80
80	80 80 80 256K 80 NV 80 128K 80 USB 64K
80	80 80 80 80 80 rd , 80, CD, 80
80 80	80 iOS/80/Windows
80 80	CE FCC RoHS
80	80
80	576 80 80 512 80 80 80 203dpi
80	200 80 80 USB & LAN 80 80 USB 80 160mm/s
80	72
80	80 80 80 80
80	80 80 / POS
80	80 80
80	UPC-A/UPC-E/JAN13/EAN13/JAN8/EAN8/CODE39/ITF/ CODABAR/CODE93/CODE128
80	80 80 80 /PDF417 (S 80 USB 80 80
80	80 GB18030 80 / 80 80 80
80 80	384 80 80 ANK 80 80 A 80 12*24dots, 1.5(W)*3.0(H) mm
80 80	80 80 9*17dots , 1.1(W)*2.1(H)mm
80 80	80 80 24*24dots, 3.0(W)*3.0(H)mm
80 80	80
80 80 80	PC347 80 80 80 80
80 80 80	PC850 80 80 80 80 / PC860 80 80 80
80 80 80	PC863 80 80 80 80 / PC865 80 80 80
80 80 80	80 / 80 / 80 / 80 / WPC1252/PC866 80 80 80 #2 / PC852 80 80
80 80 80	80 80 / PC858(Latin2)/IranII/80 80 80
80 80 80	80 80 / PT151 80 80 1251
80	80 80
80 80	79.5 ± 0.5mm
80 80	0.06~0.08mm
80 80	80 83
80	190*140*135mm
80	1.65
80	23.5*220*170
80 80	480*450*350mm/14.35kg
80	80 80 80 80
80 80 80 80	0 80 4 5 80 , 10%~80% 80
80 80 80 80	-20 80 60 80 , 10%~90% 80







POWER
STOP
FEED

Attention! Press FEED or POWER to start the work cycle, when it is ready again, if not, open the lid and turn the gear to next outer.

OFF ON





