

80mm 直径 热敏 打印机

OCPP -80X

特点

- 热敏打印 2D 打印
- 100M 打印速度
- 256KB NV Logo 2M 打印
- 打印清晰
- USB + RS232 + LAN 接口
- 250mm / s 打印

规格

打印速度	250mm/s
打印精度	79.5±0.5mm
打印直径	Φ80mm
打印厚度	0.06-0.08mm
打印长度	576mm/512mm
打印宽度	3.75mm
打印接口	ESC / POS
打印语言	+ USB +
打印分辨率	
打印内存	100KB
打印容量	2048KB
NV Flash	256KB
打印电压	AC110V / 240V 50/60Hz
打印电流	24V / 2.5A
打印功率	24V / 1A
打印温度	0-45℃ 10-80℃
打印湿度	0-45% 10-80%
打印寿命	-10-60℃; H 10-90%
打印尺寸	ANK A 1.5 * 3.0mm / B 1.1 * 2.1mm
打印格式	UPC-A / UPC-E / JAN EAN13 / JAN8 EAN8 / CODE39 / ITF / CODE93 / CODE128 / PDF417
打印兼容	PC347 PC850 PC860 PC863 PC865 WPC1252 PC866 2 PC852 2 PC858 PT151 1251
打印重量	1.45kg; 190×145×143mm



OCPP-80X





OCPP-80X





OCPP-80X





OCPP-80X





OCPP-80X

