□□□□□58mm□□□□□□□

□□□□OCPP - M06□

□□□□□□□□□OCPP -M06□□□OCPP -M06□Android□□iOS + Android□□□□□Linux□Java□□□□□□□58mm□□□□□□pos□□□□USB□RS-232□□□□□□□□□

□□□□W×D×H□		105×75×45mm
□□		134□
□□		□□□
□□□□		□□□□
□□□□		ESC / POS□□□□□
□□□□□□□		48□□
□□□□		□□90□□/□
□□□		8:00 / mm□203dpi□
□□□□		12x24 / 24x24
□□□		32□/ 16columns
□□□□		1.5 x 3.0 mm□w x h□/ 3.0x3.0mm□wxh□
□□□□		58.0±0.1mm x□□40.0mm
□□□□		0.06□0.08□□
□□□		alphaumeric / chinese kanji
□□		USB□RS-232□□□□□□□
□□		256KB
□□□□□		9V DC / 2A
□□□□		7.4V DC / 1500mAh;□□□□□□4-5□□□□□□□□□□□□□□□□□□120-150□
□□□□		□□□□□□□□□
□□□□		□□□-10□50 Degc□□□□10□□90□
□□□□		□□□-20□70 Degc□□□□5□□95□
□□□□		□□□□□□30□ASCII□□□□□□□□□□□□□□□
□□		□□□□□□□□“1234”□□□□□□□□□□□□□□□□□6□□□
□□□□□□		3.5 * 1.1mm
□□□□	OCPP -M06-BB	Android□USB + COM +□□□□□
	OCPP -M06-BB-AI	Android + iOS□USB + COM +□□□□□
	OCPP -M06-B	Android□USB + COM +□□□□□□□
	OCPP -m06-u	□□□□□□Android□USB + COM□□□□□
	OCPP -M06-BB-AA	Android + iOS□USB + COM +□□□□□□7 Android +1 Apple Device□□

ocom®
At your side

OCPP-M06

ISO FC CE RoHS

OCOM®
At your side

OCPP-M06

ocom®
At your side

OCPP-M06

ISO FC CE RoHS

ocom®
At your side

OCPP-M06

ISO FC CE RoHS

Aocom®
At your side

OCPP-M06

ISO FC CE RoHS

ocom®
At your side
OCPP-M06
(Hebrew)
(East Europe)
(Iran)
ocom
MODE
POWER
FEED
OCPP-M06
58MM Portable Thermal Printer
ISO
FC
CE
RoHS

□□□□□□□□□

□□□□□

□□□

80MM Thermal Printer

OCPP-M06

OCPP-M06
80MM Portable Thermal Printer

Li-ion Battery