

(<u>□</u>: OCPP-M06)

OCPP-M06 android (_ IOS + android),, Linux, JAVA58mm pos,
USB,RS232 00000 (00) 000000000000000000, 00000 (0000000) 00000080000800000000000
FCC NONDONAL PROPERTY OF THE P

□□□□ (W×D×H)		105×75×45mm
		134g
		ESC/POS [[[[[[]]]
		48mm
		8□/□□ (203 dpi)
		12x24/24x24
		32[]/16columns
		1.5 x 3.0 □□ (W x H)/3.0x3.0mm (WxH)
		58.0±0.1mm x □□40.0mm
		0.06
		USB, rs-232,bluetooth ([[[]])
		256KB
		9V DC/2A
		7.4V _ /1500mAh;
		Temperature:-10~50 □□□, humidity:10%~90%
		Temperature:-20~70 □□□, humidity:5%~95%
		0000, 00000000, 000 30 ASCII 000
		000000 "1234", 0000000 0000 0006000
		3.5 * 1.1mm
00000	ОСРР-М06-ВВ	Android, USB + COM + [], [][]
	OCPP-M06-BB-AI	Android + IOS, USB + COM + [], [][]
	ОСРР-М06-В	Android, USB + COM + DD, DDDD;
	OCPP-M06-U	, Android, USB + COM,
	OCPP-M06-BB-AA	android + IOS, USB + COM + [], [], 7 android +1 [][][]

0000:

- *
- *
- *
- *<u>|||||dows</u>
- *Linux [][][]
- *00000000
- *USB Printdemo([[[[[[]]]]])
- *sdk Android
- *<u>cd</u> [][