

OCPP-M06

OCPP- M06

OCPP-M06 Android iOS + Windows Linux JAVA 58 POS USB RS232 8 CE FCC required certifications

Table

Dimensions (mm)	105x75x45 Haomi	
Weight (g)	134g	
Material	ABS	
Display	1.54 inch	
Resolution	ESC / POS	
Barcode	48	
Barcode Width	90mm /	
Barcode Height	8 / mm 203DPI	
Barcode Density	12x24/24x24	
Barcode Columns	32 / 16 columns	
Barcode Pitch	1.5x3.0mm x / 3.0x3.0mm x	
Barcode Accuracy	58.0±0.1mm x 40.0mm	
Barcode Spacing	0.06 x 0.08mm	
Barcode Orientation	Vertical / Horizontal	
Interface	USB RS-232	
Memory	256KB	
Power Supply	DC 9V / 2A	
Battery	7.4V DC / 1500mAh; 4-5h; 120-150m	
Temperature	0-40°C	
Humidity	10-90%	
Shock	20g 70ms 5ms 95%	
Vibration	30g ASCII	
Language	1234 6	
Dimensions (mm)	3.5 * 1.1	
Options	OCPP-M06-BB	Android USB + COM +
	OCPP-M06-BB-AI	Android IOS USB + COM +
	OCPP-M06-B	Android USB + COM +
	OCPP-M06-U	Android USB + COM
	OCPP-M06-BB-AA	Android IOS USB + COM + 7 + 1

Table

OCPP-M06 Android iOS + Windows Linux JAVA 58 POS USB RS232 8 CE FCC required certifications

OCPP-M06 Android iOS + Windows Linux JAVA 58 POS QR 58