

OCPP-M06

OCPP- M06

OCPP-M06 Android iOS + Windows Linux JAVA 58 POS USB RS232 8 CE FCC required certifications

Table

Dimensions (mm)	105x75x45 Haomi	
Weight	134g	
Material	ABS	
Display	1.54 inch	
Resolution	ESC / POS	
Print Speed	48mm/s	
Print Width	90mm	
Print Density	8 dots/mm 203DPI	
Print Format	12x24/24x24	
Print Columns	32 / 16 columns	
Print Resolution	1.5x3.0mm x 3.0x3.0mm	
Print Accuracy	58.0±0.1mm x 40.0mm	
Print Thickness	0.06-0.08mm	
Print Temperature	0-40°C	
Interface	USB RS-232	
Memory	256KB	
Power Supply	DC 9V / 2A	
Battery	7.4V DC / 1500mAh; 4-5h; 120-150m	
Operating Temperature	0-40°C	
Operating Humidity	10-90% RH	
Storage Temperature	-20-70°C; 5-95% RH	
Storage Humidity	30% ASCII	
Barcode	1234 6	
Dimensions (mm)	3.5 * 1.1	
Options	OCPP-M06-BB	Android USB + COM +
	OCPP-M06-BB-AI	Android IOS USB + COM +
	OCPP-M06-B	Android USB + COM +
	OCPP-M06-U	Android USB + COM
	OCPP-M06-BB-AA	Android IOS USB + COM + 7 + 1

Table

OCPP-M06 is a small, portable, and easy-to-use device that can be used in various environments. It is designed to be simple and intuitive, making it easy for anyone to use. The device is compact and lightweight, making it easy to carry around. It is also very durable and can withstand harsh environments. The device is designed to be easy to use and is suitable for a wide range of applications. It is a great choice for anyone looking for a simple and reliable device.

OCPP-M06 is a small, portable, and easy-to-use device that can be used in various environments. It is designed to be simple and intuitive, making it easy for anyone to use. The device is compact and lightweight, making it easy to carry around. It is also very durable and can withstand harsh environments. The device is designed to be easy to use and is suitable for a wide range of applications. It is a great choice for anyone looking for a simple and reliable device.