□□□

□□□□□□□□□□□□
Windows□Java□Linux□Android□□ Android +IOS□□□□□ □□
□□□USB □ RS232 □□ □□
SDK for Android □□
□□□□□□□□□□ 8 □□□□□□7 □ Android□□□ Apple device) visa bluetooth
□□□□□□□□□□1500mAh□□4~5□□□
□□□□□□□□□□□□□□□□□□□□□□□□□□□□
□□□□□□□ 90mm/sec
50km □□□□□□□□
□□□□□□
□□/POS□□□□□

□□□

□□	
□□	OCPP- M06
□□	58mm □□□□□□□□□□□□□
□□	□□□
□□	USB □ RS-232 □□□□□□□
□□	7.4V DC/ 1500mAh□□□□□□□□
□□□□□	□□ 9v/1.5-2A
□□□□	□□□□4-5□
□□	□□□□□□□□ 20K□□□□256K
□□□□	□□□□□□□□□□□□□□□□□□□&□□□□□
□□□□	□□□
TPH □□	50□□
□□	□□□□□□□“1234”□□□□□□□□□□□□□ □□6□
□□	□□□□□□□□□□□□□□□□□□□□□□□□□□□□
□□□□□□	3.5*1.1mm
□□□□□□	Windows & Android & IOS □□
□□□□	CE□FCC□Rohs□
□□□□	
□□□□	□□□
□□□	203DPI□8 □/□□□
□□□□	70 □□/□□□□ 90 □□/□□
□□□□	48mm
□□□□	120 □□□□□□□□□□□□
□□□□	□□A□32□ □□/□ □□□□16 □/□
□□□□	□□□□/POS
□□□□□□	
□□□□	□□A□12*24□□1.5(W)*3.0(H) □□/□□□24*24□□ 3.0(W)*3.0(H)mm
□□□	□□□□/□□
□□	
□□□□	□□□□
□□□□	57.5 ± 0.5□□
□□□□	□□□□
□□□□	□□ 40 □□
□□□□	0.06-0.08mm
□□□	
□□	105*75*45mm

□□	□□□360g □□□440g
□□□	190*120*70 □□
40□□□□	380*475*340mm/18.36kg
□□	
□□□□□	0 to 4 5 □□□, 10%~80% □□□
□□□□□	-20 □ 60□□□□ 10%~90% □□□

OCOM
At your side
MODE
POWER
FEED
OCPP-M06
58MM Portable Thermal Printer
COM
USB

OCPP-M06
58MM Portable Thermal Printer
MODE
POWER
FEED
COM
USB

OCOM
At your side
MODE
POWER
FEED
OCPP-M06
58MM Portable Thermal Printer

(Hebrew)
(East Europe)
(Iran)
MODE
POWER
FEED
OCPP-M06
58MM Portable Thermal Printer

>>>Selftest<<<
58-II Thermal Printer
Version : MN.C-Z02-AA
Revised date: 24-Jul-2015
Command standard:EPSON(ESC/POS)
Print mode: Normal mode&
Hex mode
Line thermal
>>>Selftest<<<
58-II Thermal Printer
Version : MN.C-Z02-AA
Revised date: 24-Jul-2015
>>>Selftest<<<
58-II Thermal Printer
Version : MN.C-Z02-AA
Revised date: 24-Jul-2015
Command standard:EPSON(ESC/POS)
Print mode: Normal mode&
Hex mode
Line thermal
>>>Completed<<<
012345678901
Bluetooth Name:##NO##
MODE
POWER
FEED
OCPP-M06
58MM Portable Thermal Printer