

58

OCPP - M07



000

;

Windows Java Linux Android IOS

USB RS232

Android IOS WIN CE SDK

1D 2D QR

;

57 * 50

8 7 Android Apple

1500mAh 4~5

;

90

100KM

;

ESC / POS

□□□

□□□□□×□×□□	105×75×45□□	
□□	134□	
□□	□□	
□□□□	□□□□	
□□□□	ESC / POS□□□□□	
□□□□□□□	48□□	
□□□□	□□90□□/□	
□□□	8□/ mm□203dpi□	
□□□□	12x24 / 24x24	
□□□	32□/ 16□	
□□□□	1.5 x 3.0 mm□□x□□/3.0x3.0mm□□x□□	
□□□□	58.0±0.1mm x□□50.0mm	
□□□□	0.06□0.08□□	
□□□	□□□□/□□□□	
□□	USB□RS-232□□□□□□□□	
□	256KB	
□□□□□	9V DC / 2A	
□□□□	7.4V DC / 1500mAh;□□□□□□4-5□□□□□□□□□□□□□□□□□120-150□□□□□	
□□□□	□□□□□□□□□□	
□□□□	□□□-10~50°C□□□□□10□~90□	
□□□□	□□□-20~70°C□□□□□5□~95□	
□□□□	□□□□□□□□□□□□□□30□ASCII□□□□	
□□	□□□□□□□□□□“1234”□□□□□□□□□□□□□□□□□□6□□□□	
□□□□□□	3.5 *1.1□□	
□□□□	OCPP -M07-BB	Android□USB + COM +□□□□□□□
	OCPP -M07-BB-AI	Android + IOS□USB + COM +□□□□□□□
	OCPP -M07-B	Android□USB + COM +□□□□□□□□□;
	OCPP -M07-U	□□□□□□□□□□Android□USB + COM□□□□□□□
	OCPP -M07-BB-AA	Android + IOS□USB + COM +□□□□□□□□□7□android + 1□□□□□

□□□□□□□□



