

58

OCPP-M09

OCPP -M09AndroidIOS + AndroidWindowLinuxJAVAS58pos
USBRS-2328
CEFCC

WindowsJavaLinuxAndroidAndroid + IOS

USBRS232

AndroidSDK

QR

87AndroidApple

1500mAh45

90mm /

100km

ESC / POS;

×××	105×75×45
	134
	ESC / POS
	48
	90mm / sec
	8/203dpi
	12x24 / 24x24

晶片	32/ 16	
尺寸	1.5 x 3.0mmxmm/ 3.0x3.0mmxmm	
厚度	58.0±0.1mm xmm40.0mm	
间距	0.06mm0.08mm	
封装	SMD/贴片	
接口	USB/RS-232/有线接口	
容量	256KB	
供电电压	9V DC / 2A	
功耗	7.4V DC / 1500mAh;待机功耗4-5mA;工作功耗120-150mW	
工作温度	-40~+85℃	
存储温度	-10~50℃;湿度10~90%	
湿度	-20~70%;湿度5~95%	
通信协议	支持多种通信协议,如30ASCII等	
显示	支持显示“ 1234”等字符,支持6位显示	
尺寸	3.5 * 1.1mm	
接口	OCPP -M09-BB	Android/USB + COM +有线接口
	OCPP -M09-BB-AI	Android + IOS/USB + COM +有线接口
	OCPP -M09-B	Android/USB + COM +有线接口
	OCPP -M09-U	支持Android/USB + COM有线接口
	OCPP -M09-BB-AA	Android + IOS/USB + COM +有线接口7android +1有线接口







□□□□□□□



5/5/2019

MiniTAXIpost

