Ocbs-La04

$\square M / N \square OCBS-LA04 \square$

П	П	Г
ш	ıl I	ш

- 1.Auto-
- 3.00000;
- $4.KBW \square RS232 \square USB \square \square ;$
- 5.Durable _____;

0000	
	650-670nm_
	2.5[600] [100 UPC / EAN
	0.10 0.4MIL
0000000	2000000000000000
00000	UPC / EANUCC / EAN 128_39_39_ASCII_39_trioptic_128_128_
	[]ASCII[][][][][]UPC / EAN[][][2 5[]5[][2[][][93[][][][][11[][][ATA[]RSS[][][][][][5 2
0000	
	PS2[]RS232[]USB
	DC + 5V±5[]
	100[[
	<40[[]
	RS232
	□□45° □□60°
	L165.42mm[]¯xW69.72mm[]¯xH89.67mm
	- 40 [C] 70[]
	509500000000
	Confirm[]+/- 15kV[][][][]+/-[][][8KV[]
EMI / RFI□	FCC ADDCE
	CDRH 2[[[[[[]]]]



Product Picture











All-round show





Parameter

Visible laser (650-670nm)	
100 scans per second	
2.5 ~600mm (100% UPC/EAN)	
Bi-directional ATT	
0.10mm (4mil) at PCS 0.9	
20%, minimum reflective difference (@650nm)	
UPC/EAN, UPC/EAN with supplementals, UCC/EAN128, code 39, code 39 full ASCII, code 39 trioptic, code 128, code 128 full ASCII, codabar, interleaved 2 of 5, discrete 2 of 5, code 93, MSI, code 11, ATA, RSS variants, Chinese 2 of 5	

interiaces oupported.	F02, N0202, U0D	
Voltage:	DC+5V+/-5%	
Current:	100 mA	
Idle Current:	<40 mA	
Power Source:	Host power or external (RS232) power supply	
Scanning Angle	Inclination 45° Elevation 60°	
Dimensions:	L165.42mm X W69.72mm X H89.67mm	
Weight:	140g (without stand)	
Stand	With	
Color:	Ivory and black	
User Environment		
Operating Temperature:	0°C~50°C	
Storage Temperature:	1°-40°C~70°C	
Humidity:	5~95% relative humidity, non-condensing	
Electrostatic Discharge:	Confirm to +/-15KV air discharge and +/-8KV of contact discharge Withstands multiple 1.5m drops to concrete	
Drop Specifications:	Withstands multiple 1.5m drops to concrete	
Safe:		
EMI/RFI:	FCC Class A and CE	
Laser Safety:	CDRH class 2 laser product	
THE RESERVE OF THE PERSON NAMED IN COLUMN 2 IS NOT THE PERSON NAME		

Shipping and payment

- Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
- EXPRESS: around 3-7 working days to arrive
- INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which tination port

 By sea: depend on which destination port

 T/T destination port
- 4. By sea: depend on which destination port
- 5. T/T
- Western Union

Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.

We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,

Together we quest for the best.











