

□□□□□□□□□□□□□□□□
□M / N□OCBS-T203□

□□□□□

| | |
|----------------|--|
| □□□□□ | CMOS |
| □□ | 752 * 480 CMOS |
| □□ | □□□LED |
| □□ | Code128□UCC / EAN-128□AIM-128□EAN-8□EAN-13□ISBN / ISSN□UPC-E□UPC-A□Interleaved 2 of 5□ITF-6□ITF-14□Matrix 2 of 5□□□25□□□25□Code 39□Codabar□Code 93□Code 11□Plessey□MSI-Plessey□GS1-DataBar□RSS□□RSS-14□RSS-Limited□RSS-Expand□ |
| | PDF417□QR□□QR1 / 2□□□□□□□□□□ECC200□ ECC000,050,080,100,140□□□□□□ |
| □□ | ≥5□□ |
| □□□□ | 2.5□/□ |
| □□□□ | ±50°@ 0°□□□0° Storto |
| | ±360°@ 0°□□□0° Storto |
| | Storto ±60°@ 0°□□□0° □□ |
| □□ | USB HID-KBW□□□USB□□□USB HID-POS TTL-232□RS-232 |
| □□ | □□44°□□□33.2° |
| □□□ | EAN-13 0□□-20□□□13mil□ |
| | PDF 417 0□□ - 7□□□6.67mil□ |
| | □□39 0□□-12□□□5□□□□□1□ |
| | □□□□ 0□□ - 4□□□10MIL□ |
| | □□□□ 0□□-10□□□15□□□ |
| □□□L * W * H.□ | 89 * 108 * 143mm□□2□ |
| □□ | 245□□□□□□□□□ |
| □□□□ | 20°C□+ 50°C □-4°F~122°F□ |
| □□□□ | -40°C□+ 80°C □-40°F~176°F□ |
| □□ | 5□~95□□□□□□□□ |
| ESD | ±14□□□□□□□□□±8□□□□□□□□ |
| □□ | □□□□1.2□□□□□□□□□□□□ |
| □□ | IP 52 |



OCBS-T203





OCBS-T203



