

(POS-1508) 15.8

M / N POS-1508

OCOM POS Android windows OS MSR VFD / O

Msata SSD 64GB SSD 128GB 256GB

MSR VFD220

	POS-15 08 -W	POS-15 08 -A
	15.8 Windows POS	15.8 pos
	ABS	
	15.8	
	1920 * 1080	
	3.50cd / m ²	
	1.60 1.50	
	G+G	
	15.8 15.6 1920 * 1080	
	Intel Celeron Bay Trail J1900 2.0GHz Intel core I3 / I5 4 CPU	ARM Cortex-A17 -RK 3288 1.8GHz CPU
	1 * SO-DIMM DDRIII 1333 * / 1600 4GB 2GB / 8GB	2GB DDRIII 4GB
	Msata SSD 64GB 256GB	16GB eMMC 32GB TF
	Real Tek ALC662 ALC5640	Real Tek ALC5640

网卡	10 / 100Mbps, Realtek RTL8111F 网卡 Mini PCI-E 网卡 WiFi 网卡	10M / 100M RTL8201F 网卡 / 100M / 1000M RTL8211E 网卡
操作系统	Windows 7/8/10 系统 WEPOS Linux	Android 8.1
分辨率	640 * 480 CMOS 摄像头/摄像头	
功耗	4 英寸 3W 功耗	
尺寸	58/80 毫米 摄像头/摄像头	
接口		
I/O 接口 RK3288	摄像头 * 1	
	12V DC 接口 * 1	
	RJ-45 * 1	
	USB * 5	
	TF * 1 接口 SIM * 1 接口	
	RJ11 * 1	
重量		
尺寸	0.4 英寸	
厚度	- 1.0 英寸 60 毫米	
亮度	10% ~ 80% 亮度	
对比度	10% ~ 90% 对比度	
电压		
输入电压	110-240V / 50-60HZ AC 接口 摄像头 DC12 V / 5A 摄像头	
接口	摄像头/摄像头/摄像头	
接口	摄像头/摄像头	
接口		
认证	FCC A 类 / CE 认证 / LVD / CCC	

摄像头/摄像头









