

(POS-1508) Pos 4G Pos

M / N POS-1508

OCOM POS Android windows OS MSR VFD I/O

Msata SSD 64GB SSD 128GB 256GB

MSR VFD220

	POS-15 08 -W	POS-15 08 -A
	15.8 Windows POS	15.8 pos
	ABS	
	15.8	
	1920 * 1080	
	3.50cd / m ²	
	1.60 1.50	
	G+G	
	15.8 15.6 1920 * 1080	
	Intel Celeron Bay Trail J1900 2.0GHz Intel core I3 / I5 4 CPU	ARM Cortex-A17 -RK 3288 1.8GHz CPU
	1 * SO-DIMM DDRIII 1333 * / 1600 4GB 2GB / 8GB	2GB DDRIII 4GB
	Msata SSD 64GB 256GB	16GB eMMC 32GB TF
	Real Tek ALC662 ALC5640	Real Tek ALC5640

□□□	10 / 100Mbps, Realtek RTL8111F □□ □□Mini PCI-E□□□□□□□□WIFI □□	10M / 100M RTL8201F□10M / 100M / 1000M RTL8211E □□
□□□□	Windows 7/8/10□ □□ □□WEPOS□Linux	□□8.1
□□□	640 * 480 CMOS □□/□□□□□□□□	
S□□	4 □□ 3W □□□	
□□□	58/80 □□□□□□□□□□□□□□	
□□□□		
□□ I/O □□□J1900 □ RK3288□	□□□*1 12V DC □□ * 1 □□□□RJ-45 * 1 USB * 5 □□□	TF□*1 □SIM□*1□□□□
	□□□RJ11 * 1	
□□		
□□□□	0□40 □□□	
□□□□	- 1 0□ 60 □□□	
□□□□	10% ~ 80% □□□	
□□□□	10% ~ 90% □□□	
□□		
□□□□□	110-240V / 50-60HZ AC□□ □□□□DC12 V / 5A□□□□□□	
□□□	□□□□□□□□□□/□□/□□□□□□□□	
□□	□□□□□□□□□□□□	
□□		
□□	FCC A □ / CE □□ / LVD / CCC	

□□□□□□□□□□









