

(POS-1508) 80

Ocom

Pos

M / NPOS-1508

OCOMPOSAndroidwindows OSMSR
VFDI/O

Msata SSD 64GBSSD 128GB 256GB
MSR VFD220
/

	POS-15 08 -W	POS-15 08 -A
	15. 8 WindowsPOS	15. 8 pos
	ABS	
	15. 8	
	1920 * 1080	
	3 5 0cd / m ²	
	1 60 1 50	
	G+G	
	15 .8 15.6 1920 * 1080	
	Intel Celeron Bay Trail J1900 2.0GHz Intel core I3 / I5 4 CPU	ARM Cortex-A17 -RK 3288 1.8GHz CPU
	1 * SO-DIMM DDRIII 1333 * / 1600 4GB 2GB / 8GB	2GB DDRIII4GB
	Msata SSD 64GB 256GB	16GB eMMC32GB TF
	Real Tek ALC662ALC5640	Real TekALC5640

网卡	10 / 100Mbps, Realtek RTL8111F 芯片 支持Mini PCI-E接口支持WIFI 芯片	10M / 100M RTL8201F芯片10M / 100M / 1000M RTL8211E 芯片
操作系统	Windows 7/8/10 支持 支持WEPOS支持Linux	安卓8.1
显示屏	640 * 480 CMOS 摄像头/摄像头	
功耗	4 小时 3W 功耗	
尺寸	58/80 毫米/毫米/毫米	
接口		
接口 I/O 接口 1900 针 RK3288	USB*1	
	12V DC 接口 * 1	
	网络RJ-45 * 1	
	USB * 5	
	TF	TF*1 接口SIM*1接口
	网络RJ11 * 1	
颜色		
重量	0.40 公斤	
温度	- 1 0 度 60 度	
湿度	10% ~ 80% 湿度	
湿度	10% ~ 90% 湿度	
电压		
输入电压	110-240V / 50-60HZ AC接口 接口DC12 V / 5A接口	
接口	接口/接口/接口	
接口	接口	
接口		
接口	FCC A 类 / CE 类 / LVD / CCC	

接口接口接口









