

# POS-1513 15.1英寸商用POS终端

- 1513 )

OCOM 1513 POS 终端采用 Intel® Core™ i3/i5 处理器, MSR, 摄像头. 支持多种接口/扩展功能.

## 规格

处理器: Intel® Core™ i3/i5

芯片组: RK3288

内存: 8GB/16GB/32GB

存储: 64 GB SSD, 128GB SSD, 256 GB HDD

摄像头: 摄像头

接口: MSR, VFD220

其他: 其他

## 参数

项目	- 1513W	- 1513
型号	15.1 英寸商用 POS 终端	
尺寸	15.1 英寸	
分辨率	1024*768	
亮度	250 cd/m <sup>2</sup>	
重量	1.60kg / 1.50kg	
接口	USB, VGA, 摄像头	
处理器	9.7英寸商用终端	
存储	2*20 VFD, 2*20 LCD 触摸显示屏	
处理器	Intel Bay Trail J1900 2.0GHz Intel Core i3 / i5 4核 CPU	RK3288 / RK3399
内存	1*SO-DIMM DDRIII 1333*/1600 4GB, 2GB/8GB	DDRIII 1GB/2GB/4GB
存储	Msata SSD 64GB, 128GB, 256GB	8GB, 16GB, 32GB EMMC
音频	Real Tek ALC662	Real Tek ALC5640
网络	10/100Mbs, Realtek RTL8111F Mini PCI-E, WIFI	10/100Mbs, Realtek RTL8111F, BT3.0/BT4.0

OS	Windows 7 / 8 / Linux (POS, Linux)	OS 8.1
OS		
I/O (J1900 / RK3288)	GPIO*1	
	12V DC *1	
	RJ-45*1	
	USB*4	
I/O (J1900)	15PIN D-sub VGA *1	
	HDMI*1 / RS 232*1	
	*1	
	*1	
RK3288	*1	
	TF*1	
	RJ11*1	
	RS 232*1	
MSR		
MSR	MSR	
MSR		
MSR	0 ~ 40	
MSR	- 10 ~ 60	
MSR	10%~80%	
MSR	10%~90%	
MSR		
MSR	5.5, 7.0	
MSR	440*290 * 425 mm	
MSR		
MSR	110-240V/50-60HZ i , DC12 V /5A	
MSR		
MSR		
MSR	FCC A /CE /LVD/CCC	











