

15.6 Windows/Android POS

(M/N:POS- 1516)

OCOM POS 1516 Android windows OS MSR VFD / O

15.6

15.6

15.6

15.6

15.6

15.6

15.6

15.6

15.6

15.6 MSR

15.6

	POS-15 16-W	POS-15 16-A
	15.6 Windows POS	15.6 pos
	ABS	
	15.6	
	15.6	
	1366*768 1920*1080	
	30 0cd/m ²	
	1 60 1 50	
	G+G	
	15.6 1366*768 1920*1080	
	2*20 VFD 2*20 LCD	
	15.6	
	Intel Celeron Bay Trail J1900 2.0GHz Intel core I3 / I5 4 CPU	ARM Cortex-A17 -RK 3288 1.8GHz CPU
	1*SO-DIMM DDRIII 1333*/1600 4GB 2GB/8GB	2GB DDRIII 4GB
	Msata SSD 64GB 256GB	8GB eMMC 32GB TF

音源	Real Tek ALC662 ALC5640	Real Tek ALC5640
ネットワーク	10/100Mbps Realtek RTL8111F Mini PCI-E WIFI LAN	10M/100M RTL8201F, 10M/100M/1000M RTL8211E
OS	Windows 7/8/10 WEPOS Linux	Android 7.1 Android 8.1
I/O		
I/O RK3288	*1	
	12V DC *1	
	RJ-45*1	
	USB * 5	
	RS232* 1	RS232* 2
	VGA(15Pin D-sub)*1	RJ11 *1
	*1	*1 *1
電源		
電源	4.0 5.0	
寸法	460*185* 420mm	
ディスプレイ		
ディスプレイ	0 40	
ディスプレイ	- 10 60	
ディスプレイ	10%~80%	
ディスプレイ	10%~90%	
電源		
電源	110-240V / 50-60HZ DC12V /5A	
電源	/ /	
電源		
認証		
認証	FCC A /CE /LVD/CCC	













