

nd
 OCOM 的 POS 系统...ndro...d... 2... R or VFD ...

...

15.6...

...

...

...

...

...

...

...

...MSR...

...

...	POS-15 16	POS-15 16-A
...	15.6W...POS	15.6...pos
...	ABS ...	
...	...	
Display		
...	15.6...	
...	1366*768 1920*1080	
...	300cd/m ²	
... a1.60 ; ...1.50	
... sGG ...	
...	15.6 ... W ... W/o ... 1366*768 1920*1080 ...	
...	2*20 VFD 2*20 LCD ...	
...		
...	... Bay Trail J1900 2.0GHz ... intel core I3 / I5 4... CPU	ARM Cortex-A17 -RK 3288 1.8GHz CPU
... ..	1*SO-DIMM DDRIII ... 1333*/1600 4GB ... 2GB/8GB	...2GB DDRIII...4GB
...	M SATA SSD 64GB ... 256GB	8GB eMMC...32GB TF
...	...ALC662...ALC5640	...Real Tek...ALC5640
...	10/100Mbs, Realtek RTL8111F ... Mini PCI-E...WIFI	10M/100M RTL8201F, 10M/100M/1000M RTL8211E

□□□□	Windows 2010 □ 7 □ 8 □□ □□□□WEPOS, Linux	□□7 .1 □ Android 8.1 □□
□□□		
□□□ /O□□ (J1900 □ RK3288)	p □ □□*1	
	12V DC □□*1	
	□□□□RJ-45*1	
	USB * 4	
	□□(RS232) * 1	□□(RS232) * 2
	VGA(15Pin D-sub)*1	RJ11 □□□□ *1
	□□□□*1	M □□□□ in *1 , □□□□*1
□□		
□□	□ 4.0 □□ □□ 5.0 □□	
P □□□□□□□□	460*185*420 mm □□□□	
□□		
□□□□	0 □ 40 □□□	
□□□□	- 1 0 □ 60 □□□	
□□□□	10%~80% □□□	
□□□□	10%~90% □□□	
□□		
□□□□□□	110-240V/50-60HZ□□□□ i □□ , DC12 V /5A □□□□□	
□□□	□□□□/□□/□□□□□□□□□□□□□□	
□□	□□□□□□□□□□□□	
□□		
□□	FCC A □/CE □□/ LVD/CCC	



招牌奶茶		精选奶茶		冰城小吃		饭饭精选	
01. 葡萄西柚鲜奶茶	¥18	台式奶茶	¥13	奶茶	¥15	春天奶茶	¥16
02. 满杯奇异果	¥18	樱花阿墨山奶茶	¥18	黑糖奶茶	¥20	珍珠奶茶	¥17
03. 奶茶	¥15	珍珠奶茶	¥15	珍珠鲜奶茶	¥17	相思豆奶茶	¥15
04. 熊猫奶茶	¥20	蜜桃大青柠奶茶	¥18	薏米抹茶红豆	¥17		
05. 珍珠鲜奶茶	¥17						

清空(0) 下单

点击选择会员

收银 ¥88















