

nd
 OCOM 的 POS 系统...ndro...d... 2... R or VFD ...

...

15.6...

...

...

...

...

...

...

...

...MSR...

...

...	POS-15 16	POS-15 16-A
...	15.6W...POS	15.6...pos
...	ABS ...	
...	...	
Display		
...	15.6...	
...	1366*768 1920*1080	
...	300cd/m ²	
... a1.60 ; ...1.50	
... sGG ...	
...	15.6 ... W / W/o ... 1366*768 / 1920*1080	
...	2*20 VFD / 2*20 LCD	
...		
...	... Bay Trail J1900 2.0GHz / intel core I3 / I5 4... CPU	ARM Cortex-A17 -RK 3288 1.8GHz CPU
... ..	1*SO-DIMM DDRIII ... 1333*/1600 4GB / 2GB/8GB	...2GB DDRIII/4GB
...	M SATA SSD 64GB / 256GB	8GB eMMC / 32GB TF
...	...ALC662 / ALC5640	...Real Tek / ALC5640
...	10/100Mbs, Realtek RTL8111F / Mini PCI-E / WIFI	10M/100M RTL8201F, 10M/100M/1000M RTL8211E

□□□□	Windows 2010 □ 7 □ 8 □□ □□□□WEPOS, Linux	□□7 .1 □ Android 8.1 □□
□□□		
□□□ /O□□ (J1900 □ RK3288)	p □ □□*1	
	12V DC □□*1	
	□□□□RJ-45*1	
	USB * 4	
	□□(RS232) * 1	□□(RS232) * 2
	VGA(15Pin D-sub)*1	RJ11 □□□□ *1
	□□□□*1	M □□□□ in *1 , □□□□*1
□□		
□□	□ 4.0 □□ □□ 5.0 □□	
P □□□□□□□□	460*185*420 mm □□□□	
□□		
□□□□	0 □ 40 □□□	
□□□□	- 1 0 □ 60 □□□	
□□□□	10%~80% □□□	
□□□□	10%~90% □□□	
□□		
□□□□□□	110-240V/50-60HZ□□□□ i □□ , DC12 V /5A □□□□□	
□□□	□□□□/□□/□□□□□□□□□□□□□□	
□□	□□□□□□□□□□□□	
□□		
□□	FCC A □/CE □□/ LVD/CCC	

















