

15.6 POS

(POS- 1516)

OCOM POS Android/Window MSR or VFD

POS

- l. 15.6
- m. ABS
- n. Display
- o. 300cd/m²
- p. 160:150
- q. 15.6 W/Wo
- r. 2*20 VFD / 2*20 LCD
- s. intel core i3 / ARM Cortex-A17
- t. MSR

Table

Model	POS-15 16	POS-15 16-A
OS	15.6 Windows POS	15.6 pos
Keyboard	ABS	
Mouse		
Display		
Size	15.6	
Resolution	1366*768/1920*1080	
Brightness	300cd/m ²	
Refresh Rate	160:150	
Panel Type	GG	
Options	15.6 W/Wo 1366*768 / 1920*1080	
Input	2*20 VFD / 2*20 LCD	
Processor		
CPU	Bay Trail J1900 2.0GHz intel core i3 / I5 400 CPU	ARM Cortex-A17 -RK 3288 1.8GHz CPU
RAM	1*SO-DIMM DDRIII 1333*/1600 4GB / 2GB/8GB	2GB DDRIII/4GB
Storage	Msata SSD 64GB / 256GB	8GB eMMC/32GB TF
Audio	ALC662/ALC5640	Real Tek/ALC5640
Network	10/100Mbs, Realtek RTL8111F / Mini PCI-E/WIFI	10M/100M RTL8201F, 10M/100M/1000M RTL8211E
OS	Windows 2010 / 7 / 8 / WEPOS, Linux	7.1 / Android 8.1
Ports		
Power	power*1	
DC	12V DC *1	
Network	RJ-45*1	
USB	USB * 4	
Serial	(RS232) * 1	(RS232) * 2
VGA	VGA(15Pin D-sub)*1	RJ11 *1
Other	*1	M in *1, *1
Dimensions		
Weight	4.0	5.0

□□□□□□□□	460*185*420 mm □□□□
□□	
□□□□	0 □ 40 □□□
□□□□	- 1 0 □ 60 □□□
□□□□	10%~80% □□□
□□□□	10%~90% □□□
□□	
□□□□□□	110-240V/50-60HZ□□□□ i □□ , DC12 V /5A □□□□□
□□□□	□□□□/□□/□□□□□□□□□□□□□□
□□	□□□□□□□□□□□□
□□	
□□	FCC A □/CE □□/□□/□□□□/CCC









