

# 15.6吋/吋 POS 吋吋

- 1516

吋吋

1. 15.6吋吋吋吋吋
2. 吋吋吋吋吋
3. 吋吋吋吋吋吋吋吋吋
4. 吋吋 吋吋 吋吋吋吋吋吋
5. 吋吋吋吋吋
6. 吋吋吋吋吋吋吋
7. 吋吋吋吋吋
8. 吋吋吋吋吋吋吋
9. 吋吋吋吋吋吋吋吋吋吋sR吋吋

吋

吋	POS-15 16-W	POS-15 16-A
吋	15.6吋W吋dows吋吋OS	15.6吋吋吋POS
吋	ABS吋吋吋 吋 um吋	
吋	吋吋	
吋	吋吋吋吋吋	
吋	1366*768吋1920*1080吋	
吋	30 0cd/吋 <sup>2</sup>	
吋 a 吋	吋吋1 60 ;吋吋1 50	
吋 s 吋	吋 吋GG 吋吋	
吋吋	15.6 吋吋吋吋吋吋吋吋吋 1366*768吋1920*1080 吋吋吋	
吋吋	2*20 VFD 吋 2*20 LCD 吋吋吋吋	
吋	吋	
吋	吋吋 吋 Bay Tra吋 J1900 2.0GHz 吋吋 吋tel core 吋3 / th I5 4 吋CPU吋	RK 3 566吋 吋 1.8GHz CPU
吋 吋	1*SO-D吋 DDRIII 吋吋 吋1333*/1600 4GB吋 吋2GB/8GB吋	吋2GB DDRIII吋4GB吋
吋吋	M SATA SSD 64GB 吋吋吋 256GB	32 吋eMMC
吋	吋Real Tek ALC662吋吋 吋ALC5640	吋Real Tek吋吋ALC5640
吋	10/100Mbs, Realtek RTL8111F 吋吋 吋Mini PCI-E吋吋吋吋WIFI 吋	10M/100M RTL8201F, 10M/100M/1000M RTL8211E吋
吋吋	Windows 2010 吋 7 吋 8 吋 吋 吋吋WEPOS, Linux	吋11
吋	吋	
吋 /O 吋 J1900 吋 RK3288	p 吋 吋*1 12V DC 吋吋吋*1 吋吋吋RJ-45*1 USB * 4 吋(RS232) * 1	吋(RS232) * 2 RJ11 吋*1 M 吋吋 in *1, 吋吋吋*1
吋	吋	
吋	吋 4.0 吋 吋 5.0 吋	

P	460*185*420 mm
	0 ~ 40
	- 1 0 ~ 60
	10%~80%
	10%~90%
	110-240V/50-60HZ i , 12 V /5A
	FCC A /CE /LVD/CCC





















