

POS-1519 15.1 Windows 10 15.1

POS-1519

15.1

15.1 15.1 I3 I5

Msata SSD 64 GB SSD 128GB 256 GB

MSR VFD220

15.1

| | |
|------|---|
| 15.1 | POS-1519 |
| 15.1 | 15.1 POS |
| 15.1 | |
| 15.1 | |
| 15.1 | 15.1 |
| 15.1 | 1024*768 |
| 15.1 | 25 0cd/m ² |
| 15.1 | 1 5 0 1 4 0 |
| 15.1 | G+G |
| 15.1 | 15 |
| 15.1 | 2 * 20 VFD 2 * 20 LCD |
| 15.1 | |
| 15.1 | Intel Celeron Bay Trail J1900 2.0GHz Intel Celeron J4125 intel core I3 / I5 CPU |
| 15.1 | 1*SO-DIMM DDRIII, 4GB DDR3L/ 1333 , 8GB |
| 15.1 | Msata SSD 64GB 256GB |
| 15.1 | Real Tek ALC662 |
| 15.1 | 10/100Mbs Realtek RTL8111F Mini PCI-E WIFI |
| 15.1 | Windows 7/8/10 WEPOS, Linux |
| 15.1 | |
| 15.1 | 12V DC in Jack *1 |
| 15.1 | RJ-45*1 |
| 15.1 | USB*6 |
| 15.1 | 15PIN D-sub VGA *1 |
| 15.1 | RS 232*2 |
| 15.1 | *1 *1 |
| 15.1 | |
| 15.1 | MSR MSR |
| 15.1 | |
| 15.1 | 6.5Kg , 8 . 0 |
| 15.1 | 425*275 * 405mm 440*295*425mm |

| | |
|-------|---|
| □□ | |
| □□□□ | 0□40 □□□ |
| □□□□ | - 10□60□□□ |
| □□□□ | 10%~80% □□□ |
| □□□□ | 10%~90% □□□ |
| □□ | |
| □□□□□ | 110-240V / 50-60HZ□□□□□□□□DC12V / 5A□□□□□ |
| □□□ | □□□□□□□□□□/□□/□□□□□□□□ |











**All in one
Touch POS system**