

POS-1701 17.1 POS POS

(M/N:POS- 1701)

1. 17
2. 300°
3. MSR

11

OS	POS- 1701
OS	1 7 . 1 64bit POS 32_
OS	64bit/32bit 32
OS	64bit/32bit 32
OS	
OS	1 7 . 1 64bit/32bit
OS	1400*900
OS	20 0cd/m ²
OS	6 0 90
OS	G+G 32bit
OS	2 * 20 VFD/2 * 20 LCD/32bit 32bit/32bit
OS	
OS	Intel Celeron Bay Trail J1900 2.0GHz 32bit Intel core I3 / I5
OS	4 CPU 32bit
OS	1*SO-DIMM DDR3/1333*/1600 4GB 32bit
OS	2GB/8GB
OS	Msata SSD 64GB 32bit/256GB
OS	Real Tek ALC662
OS	10/100Mbps/Realtek RTL8111F 32bit
OS	Mini PCI-E/32bit/WIFI/32bit
MSR	MSR
OS	Windows 7/8/10/32bit/WEPOS, Linux
OS	
OS	1
I/O J1900 I3 I5	12V DC 32bit*1
	RJ-45*1
	USB*6
	15PIN D-sub VGA *1
	HDMI*1/RS 232*1 32bit I3/I5
	J1900 RS232*2
	32bit*1/32bit*1
OS	
OS	4.5/5.5

□□□□□□	485*453*205□□
□□	
□□□□	0□40 □□□
□□□□	- 10□60□□□
□□□□	10%~80% □□□
□□□□	10%~90% □□□
□□	
□□□□□	110-240V / 50-60HZ□□□□□□□□DC12V /5A□□□□□
□□□	□□□□□□□□□□/□□/□□□□□□□□
□□	
□□	FCC A □/CE □□/LVD/CCC



















Application



Bar



Restaurant



Coffee Store



Mile Tea Store



Bakery



Convenience Store



Library



Supermarket