

17.1 17.1 POS

- 1701)

17.1

1. 17.1 POS
2. 17.1 POS
3. 17.1 POS
4. 17.1 POS 300°
5. 17.1 POS
6. 17.1 POS
7. 17.1 POS
8. 17.1 POS
9. 17.1 POS MsR

17.1

17.1	- 1701
17.1	17.1 POS
17.1	17.1 POS
17.1	W POS
17.1	17.1
17.1	1400*900
17.1	20 0cd/m ²
17.1	17.1 60 ; 90
17.1	17.1 s GG
17.1	2*20 FD 2*20 LCD
17.1	17.1 Bay Tra J1900 2.0GHz intel core I3 / I5 4 th
17.1	17.1 CPU
17.1	17.1 SO-DIMM DDRIII 1333*/1600 4GB , 2 GB/8GB
17.1	17.1 Msata SSD 64GB 256GB
17.1	17.1 Real Tek ALC662
17.1	17.1 10/100Mbs, Realtek RTL8111F
17.1	17.1 Mini PCI-E WIFI
17.1	17.1 MSR
17.1	17.1 2010 7 8 POS, Linux
17.1	17.1 I/O J1900 I3 I5
17.1	17.1 P *1
17.1	17.1 12V DC *1
17.1	17.1 RJ-45*1
17.1	17.1 USB*6
17.1	17.1 15PIN D-sub VGA *1
17.1	17.1 HDMI*1 RS 232*1 I3/I5
17.1	17.1 J1900 RS232*2
17.1	17.1 *1 *1
17.1	17.1 4.5 5.5
17.1	17.1 485*453*205 mm

□□	
□□□□	0 □ 40 □□□
□□□□	-1 0 □ 60 □□□
□□□□	10%~80% □□□
□□□□	10%~90% □□□
□□	
□□□□□	110-240V/50-60HZ □□□□ i □□ , DC12 V /5A □□□□□
□□□	□□□□□□□□□□/□□/□□□□□□□□
□□	
□□	FCC A □/CE □□/ LVD/CCC











