

17.1POS

(M/N:POS- 1701)

- 1. 17
- 2.
- 3.
- 4. 300°
- 5.
- 6.
- 7.
- 8.
- 9. MSR

	POS- 1701
	1 7 . 1 POS
	1 7 . 1
	1400*900
	20 0cd/m ²
	6 0 90
	G+G
	2 * 20 VFD2 * 20 LCD
	Intel Celeron Bay Trail J1900 2.0GHz Intel core I3 / I5 4 CPU
	1*SO-DIMM DDRIII1333*/1600 4GB 2GB/8GB
	Msata SSD 64GB 256GB
	Real Tek ALC662
	10/100MbsRealtek RTL8111F Mini PCI-EWIFI
MSR	MSR
	Windows 7/8/10 WEPOS, Linux
I/O J1900 I3 I5	*1 12V DC *1 RJ-45*1 USB*6 15PIN D-sub VGA *1 HDMI*1RS 232*1 I3/I5 J1900 RS232*2 *1*1
	4.5 5.5

□□□□□□	485*453*205□□
□□	
□□□□	0□40 □□□
□□□□	- 10□60□□□
□□□□	10%~80% □□□
□□□□	10%~90% □□□
□□	
□□□□□	110-240V / 50-60HZ□□□□□□□□DC12V /5A□□□□□
□□□	□□□□□□□□□□/□□/□□□□□□□□
□□	
□□	FCC A □/CE □□/ LVD/CCC











