

## 17.1 17.1 POS

- 1701)

17.1

1. 17.1
2. 17.1
3. 17.1
4. 17.1 300°
5. 17.1
6. 17.1
7. 17.1
8. 17.1
9. 17.1 MsR

17.1

17.1	- 1701
17.1	17.1 POS
17.1	17.1
17.1	W 17.1
17.1	17.1
17.1	1400*900
17.1	20 0cd/m <sup>2</sup>
17.1	17.1 60 ; 17.1 90
17.1 s	17.1 GG
17.1	2*20 FD 2*20 LCD 17.1 17.1 17.1
17.1	17.1 Bay Tra J1900 2.0GHz 17.1 intel core I3 / I5 4 <sup>th</sup> 17.1 CPU
17.1	1*SO-DIMM DDRIII 17.1 1333*/1600 4GB 17.1 ,2 GB/8GB 17.1
17.1	Msata SSD 64GB 17.1 256GB
17.1	17.1 Real Tek ALC662
17.1	10/100Mbs,Realtek RTL8111F 17.1 17.1 Mini PCI-E 17.1 WIFI 17.1
MSR	17.1 MSR
17.1	17.1 2010 17.1 7 17.1 8 17.1 17.1 POS, Linux
17.1 I/O 17.1 J1900 17.1 I3 I5	P 17.1 *1 12V DC 17.1 *1 17.1 RJ-45*1 USB*6 15PIN D-sub VGA *1 HDMI*1 RS 232*1 17.1 I3/I5 J1900 17.1 RS232*2 17.1 *1 17.1 *1
17.1	17.1 4.5 17.1 17.1 5.5 17.1
17.1	485*453*205 mm

□□	
□□□□	0 □ 40 □□□
□□□□	-1 0 □ 60 □□□
□□□□	10%~80% □□□
□□□□	10%~90% □□□
□□	
□□□□□	110-240V/50-60HZ □□□□ i □□ , DC12 V /5A □□□□□
□□□	□□□□□□□□□□/□□/□□□□□□□□
□□	
□□	FCC A □/CE □□/ LVD/CCC











