

POS
OCBS-LA04

OCBS-LA04

OCBS-LA04	
OCBS-LA04	OCBS-LA04 650-670nm
OCBS-LA04	100
OCBS-LA04	2.5 600 100 UPC / EAN
OCBS-LA04	
OCBS-LA04	0.10 4mil PCS 0.9
OCBS-LA04	20 @ 650nm
OCBS-LA04	UPC/EAN, UPC/EAN with supplementals, UCC/EAN128, code 39, code 39 full ASCII, code 39 trioptic, code 128, code 128 full ASCII, codabar, interleaved 2 of 5, discrete 2 of 5, code 93, MSI, code 11, ATA, RSS variants, Chinese 2 of 5...
OCBS-LA04	
OCBS-LA04	PS2 RS232 USB
OCBS-LA04	DC +5 V + / -5
OCBS-LA04	100
OCBS-LA04	<40
OCBS-LA04	RS232
OCBS-LA04	45° 60°
OCBS-LA04	L165.42mm X W69.72mm X H89.67mm
OCBS-LA04	140
OCBS-LA04	
OCBS-LA04	
OCBS-LA04	0°C 50°C
OCBS-LA04	-40°C 70°C
OCBS-LA04	5 95
OCBS-LA04	+ /-15KV + /-8KV
OCBS-LA04	1.5
OCBS-LA04	
EMI / RFI	FCC Class A CE
OCBS-LA04	CDRH 2

OCBS-LA04

