

15" POS

M / N POS -8617Plus-B



□□

□□□□□1900□□1.99 GHZ;

4GB RAM□64GB SSD□□□□;

□□□□□□□□

□□□□□□

□□□□□□□□□□

□□□□□□□□□□□□

□□□□□□□□□□□□□□

□□□□□□□□□□MSR□□□□RFID□□□□□□

□□□□□□□□□□□□□□□□

□□□□□

□□□□□□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□□□□□□□

□□

| | |
|----|-----------------|
| □□ | POS -8617Plus-B |
| □□ | □□ |

| | |
|-----|------------------------------|
| 螢幕 | VFD220吋LCD220吋MSR RFID 10.1吋 |
| 晶片 | ARM Cortex-A9 |
| 處理器 | 1900MHz 1.9 GHz |
| 晶片 | NM70 |
| 記憶體 | DDRIII 1066/1333 * 1 4GB |
| 儲存 | SSD 64GB |
| 顯示器 | 15.1吋 TFT |
| 亮度 | 350cd / m ² |
| 解析度 | 1024 * 768 |
| 其他 | |

| | |
|-------|-----------------------------------|
| 尺寸 | 150mm x 140mm |
| I/O 埠 | 1 * 12V DC * 1 |
| | HDMI * 1 |
| | VGA 15吋 D-sub * 1 |
| | RJ-45 * 1 |
| | USB 2.0 * 4 / USB 3.0 * 2 |
| | RS232 * 2 |
| | MIC IN * 1 |
| 工作溫度 | 0°C ~ 40°C |
| 儲存溫度 | -20°C ~ 60°C |
| 認證 | FCC A / CE / LVD / CCC |
| 作業系統 | Windows XP / WE POS / Linux |
| 電源 | 110-240V / 50-60HZ AC / DC12 / 5A |



POS-8617Plus-B





POS-8617Plus-B





POS-8617Plus-B





POS-8617Plus-B





POS-8617Plus-B





POS-8617Plus-B





POS-8617Plus-B





POS-8617Plus-B





POS-8617Plus-B

