

# 15" J1900 4G POS

## POS -8618L

□□

□□□□ J1800 □ 2.4 GHZ;

□□ SSD 32GB □□□□;

□□□□□□ SSD □ HDD □

□□□□□□□□

1024 \* 768 □□ LCD □□;

□□ / O □□□□

□□□□

□□□□□□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□□□□□□□

□□

□□	POS -8618L
□□□□	□□
□□	□□□□□□□□
□□□□□□	J1800 / J1900 / i3 / i5
□□□□	□□□□ NM70 □ J1800 □
□□	DDR III 1066/1333 * 1 2GB □□□□□□□□ 4GB / 8GB
□□	SSD 32GB □□□□□□□□□□ SSD 64GB □ 128GB □ 256GB
□□□□□□	15" TFT LCD
□□	350cd / □ <sup>2</sup>
□□□□	1024 * 768 □□□□
□□□□	□□□□□□□□
□□□□	□□□□ 150; □□□□ 140

I / O	1 * 12V DC
	* 1 DB9
	* 1 DB25
	VGA 15 D-sub * 1
	RJ-45 * 1
	USB 2.0 * 4 USB 3.0 * 2
	* 1
	* 1
	PS / 2 * 1 PS / 2 * 1
	0°C ~ 40°C
	-20°C ~ 60°C
	Windows XP
	110-240V / 50-60HZ AC DC12 / 5A





POS-8618L





POS-8618L





POS-8618L





POS-8618L





POS-8618L

