

POS

(M V N:POS-A15VA15-A)

J1900 2.0 g h z CPU Windows

2.0 g h z A83T 8 -A7

2 GB RAM + 32 GB ROM

58 80

MSR IC RFID reader(Optional)



	POS-A15VPOS-A15-A
Board①	J1900 2.0 g h z
Board②	2.0 g h z A83T ARM 8 -A7
OS①	Windows7(Beta)
OS②	4.4.4
Memory①	2 GB RAM 32 GB
Memory②	2 GB RAM EMMC 32 GB
	screen15.6 screen15.6inch
	58 80mm
I/O port(①J1900)	USB * 4
	RJ45 * 1
	RJ11 * 1
	HDMI * 1
	DB9 RS232 * 1

I/O port(@A83T)	RJ11 * 1
	TF * 1
	RJ45 * 1
	HDMI * 1(for vice screen)
	USB * 2
	DB9 RS232 * 1
	* 1
	USB OTG
0 °C ~ 40 °C	
WIFI GPS	
items(Windows)	3 15 CPU VFD RFID IC MSR cammera 3 G DB25 DB9 RS232 * 3
items(Andriod)	3 G cammera VFD RFID IC MSR
-20°Cto 60 °C	
46 * 43 * 51	
110-240V/50-60 HZ DC12V/5A	



POS-A15



www.ocominc.com

CE FC





POS-A15



www.ocominc.com



