

Windows /Android 58 /80mm POS

(M V N:POS-A15VA15-A)

□□

□□□□□□□□ J1900 □□ 2.0 g h z □□ CPU □ Windows □

2.0 g h z A83T □□ 8 □□-A7 □□□□□□

2 GB RAM + 32 GB ROM □□

□□□□□□□□

□□ 58 □□ 80 □□□□□□

□□□ MSR□□ IC □□□□RFID reader(Optional)

□□□□□□

□□□□□

□□ □□ □□ □□□ □□□ □□□ □□□

□□□ □□□□□□□□ □□□□□□□□□□□□□□

□□ □□ □□□□ □□□ □□□□ □□□□□□□□□□

□□ □□□□□□□□□□□□ □□ □□ □□□□□

□□□□□



□□□

□□	POS-A15VPOS-A15-A
□□ Board①	□□□□□□□□ J1900 □□ 2.0 g h z
□□ Board②	2.0 g h z A83T ARM 8 □□-A7 □□□
OS①	Windows7(Beta)
OS②	□□ 4.4.4
Memory①	2 GB RAM 32 GB □□□□
Memory②	2 GB RAM EMMC 32 GB
□□ □□	□□□□□□□□
□□ □□	□□ screen15.6 □□□□ screen15.6inch
□□	□□ □□□
□□□	58 □□ □□□□□□□□□□ 80mm □□□□□□□□□□□□
I/O port(①J1900)	USB * 4
	RJ45 * 1
	RJ11 * 1
	HDMI * □□ 1 □□□□
	DB9 RS232 □□ * 1

I/O port(@A83T)	RJ11 * 1
	TF * 1
	RJ45 * 1
	HDMI * 1(for vice screen)
	USB * 2
	DB9 RS232 * 1
	* 1
	USB OTG
0 °C ~ 40 °C	
WIFI GPS	
items(Windows)	3.5 GHz CPU VFD RFID IC MSR camera 3 G DB25 DB9 RS232 * 3
items(Andriod)	3 G camera VFD RFID IC MSR
-20°C to 60 °C	
46 * 43 * 51	
110-240V/50-60 HZ DC12V/5A	



POS-A15



www.ocominc.com

CE FC





