

POS NFC 1900 2.0GHz CPU Windows pos

M / N POS-B12 / B12-A

Spec

Board① 1900 2.0GHz CPU Windows
 Board② 2.0GHz A83T ARM 8 Cortex-A7
 Memory① 2GB RAM + 32GB SSD Windows
 Memory② 2GB RAM + 8GB ROM Android
 OS① Windows 7
 OS② Android 5.1
 I/O ① USB * 4, RJ45 * 1, RJ11 * 1, VGA * 1, HDMI * 1, DB9 RS232 * 1
 I/O ② RJ11 * 1 (Optional), TF * 1, RJ45 * 1, HDMI * 1, USB * 2, DB9 RS232 * 1, * 1, USB OTG * 1
 Temp 0°C ~ 40°C
 Android Android
 Display LCD VFD, RFID, MSR, 3G, DB25, DB9 RS232 * 3
 Display 3G, 4G, LCD VFD, RFID, MSR
 Temp -20°C ~ 60°C
 Size 46 * 43 * 51 mm
 Power 110-240V / 50-60HZ, 12 / 24V

Image

POS-B12 / POS-B12-A
 POS-B12 / POS-B12-A
 POS-B12 / POS-B12-A
 POS-B12 / POS-B12-A

Image



Table

Model	POS-B12 / POS-B12-A
Board①	1900 2.0GHz CPU
Board②	2.0GHz A83T ARM 8 Cortex-A7
OS①	Windows 7
OS②	Android 5.1
Memory①	2GB RAM + 32GB SSD Windows
Memory②	2GB RAM + 8GB ROM Android
Temp	0°C ~ 40°C
I / O ①	USB * 4, RJ45 * 1, RJ11 * 1, VGA * 1, HDMI * 1, DB9 RS232 * 1
I / O ②	RJ11 * 1 (Optional), TF * 1, RJ45 * 1, HDMI * 1, USB * 2, DB9 RS232 * 1, * 1, USB OTG * 1
Temp	0°C ~ 40°C
Android	Android
Display	LCD VFD, RFID, MSR, 3G, DB25, DB9 RS232 * 3
Display	3G, 4G, LCD VFD, RFID, MSR
Temp	-20°C ~ 60°C
Size	46 * 43 * 51 mm
Power	110-240V / 50-60HZ, 12 / 24V

posposposnfc