

Windows POS

M / N POS-B12 / B12-A

Spec

Board① 1900MHz 2.0GHz CPU Windows
 Board② 2.0GHz A83T ARM 8 Cortex-A7
 Memory① 2GB RAM + 32GB SSD Windows
 Memory② 2GB RAM + 8GB ROM Android
 OS① Windows 7
 OS② Android 5.1
 I/O ① 58mm MSB RFID
 I/O ② MSB RFID

Feature

1. 1900MHz 2.0GHz CPU
 2. 2.0GHz A83T ARM 8 Cortex-A7
 3. 2GB RAM + 32GB SSD Windows
 4. 2GB RAM + 8GB ROM Android

Option



Table

Model	POS-B12 / POS-B12-A
Board①	1900MHz 2.0GHz CPU
Board②	2.0GHz A83T ARM 8 Cortex-A7
OS①	Windows 7
OS②	Android 5.1
Memory①	2GB RAM + 32GB SSD Windows
Memory②	2GB RAM + 8GB ROM Android
OS①	Windows 7
OS②	Android 5.1
OS③	Android 5.1
OS④	Android 5.1
OS⑤	Android 5.1
OS⑥	Android 5.1
OS⑦	Android 5.1
OS⑧	Android 5.1
OS⑨	Android 5.1
OS⑩	Android 5.1
I / O ① 1900MHz	USB * 4 RJ45 * 1 RJ11 * 1 VGA * 1 HDMI * 1 DB9 RS232 * 1
I / O ② A83T	RJ11 * 1 (Optional) TF * 1 RJ45 * 1 HDMI * 1 USB * 2 DB9 RS232 * 1 RS485 * 1 USB OTG * 1
OS①	0°C ~ 40°C
OS② Android	WiFi
OS③	LCD VFD RFID MSB 3G DB25 DB9 RS232 * 3
OS④	3G 4G LCD VFD RFID MSB
OS⑤	-20°C ~ 60°C
OS⑥	46 * 43 * 51mm
OS⑦	110-240V / 50-60HZ 12 / 24V

