

# POS-G156 15.6 吋 POS 電腦 (Windows POS 電腦)

## (POS-G156/G151)

OCOM G156 pos 電腦 15.6 吋 POS 電腦 (Windows POS 電腦) 15.1 吋 POS 電腦 (Windows POS 電腦) 15.6 吋 POS 電腦 (Windows POS 電腦) 15.1 吋 POS 電腦 (Windows POS 電腦)...

規格

Intel Celeron / intel core I3 / I5  
 Msata SSD 64GB / SSD 128GB / 256 GB  
 58mm / 80mm  
 MSR / VFD220

規格

規格		POS-G156W/A	POS-G151W/A
規格		15.6 吋 POS 電腦	15.1 吋 POS 電腦
規格		15.6 吋 POS 電腦	15.1 吋 POS 電腦
規格		1366*768	1024*768
規格		250cd/吋	
規格		160 吋 / 150 吋	
規格		GG 吋	
規格		15.6 吋 POS 電腦 13.3 吋 POS 電腦 1366*768 吋	15.1 吋 POS 電腦 1024*768 吋
規格		2*20 VFD 吋	
規格			
windows J1900	規格	Intel Celeron Bay Trail J1900 2.0GHz / intel core I3 / I5 4th CPU	
	規格	1*SO-DIMM DDRIII 1333*/1600 4GB / 2GB/8GB	
	規格	Msata SSD 64GB / 256GB	
	規格	Real Tek ALC662	
	規格	10/100Mbs, Realtek RTL8111F / Mini PCI-E WIFI	
	規格	Windows 7/8/10, WEPOS, Linux	
RK3288	規格	Rockchip RK3288 / 1.8G RK3399	
	RAM	DDRIII 2GB, 4GB	
	ROM	16GB EMMC, 32GB	
	規格	Real Tek ALC5640	
	規格	10/100Mbs, Realtek RTL8111F	
	WIFI & 規格	Wi-Fi 802.11b/g/n, BT3.0/BT4.0	
	規格	7.1	
規格			

Windows(J1900&RK3288)	12V DC *1 (RS232) * 1 RJ-45*1 USB*5 *1 , *1
Windows ( J1900)	*1 VGA(15Pin D-sub)*1 RJ11 for Cash drawer *1 PS/2 *1
( RK3288)	RJ11 for Cash drawer *1 ,RJ11 from printer port for Cash drawer *1 TF*1
80mm	150mm/s 79.5-/ 0.5mm 72mm 100km USB
58mm	80mm/s 57.5-/ 0.5mm 48mm 50km LPT
MSR	MSR 15.6
	8Ohm/5W
	15.6Kg/6.5Kg/8.5Kg
	300*465*500mm
	0 40
	-10 60
	10%~80%
	10%~90%
	110-240V/50-60HZ ,DC12/5A 58mm DC12V/7A W/80mm
	FCC A /CE /LVD/CCC

# All In One Touch Screen POS System

---



# Product Display

The whole machine featured anti-static protection, stronger EMI anti-interference, anti-ESD up to 8KV



# Accessories



Thermal Printer



Barcode Scanner



Cash Drawer



Card Reader



Product  
**Accessories**

# SUPPORT SYSTEMS



WINDOWS



ANDROID




LINUX

# Product Interface


## Windows interfaces J1900




DC




LPT




COM



VGA



LAN



RJ11(optional)



USB 3.0\*1



USB 2.0\*4



PS/2



MIC-IN



LIN-OUT


## Windows interfaces i3/i5




DC




HDMI



VGA



LAN



RJ11(optional)



USB 2.0\*4



USB 3.0\*1



MIC-IN




LIN-OUT


## Android interfaces RK3288




DC




COM



LAN



RJ11(optional)\*2



USB 3.0\*1



USB 2.0\*4



TF Card



MIC-IN



LIN-OUT

# Screen Size



↙↘ 15.6 inch

or



↙↘ 15.6 inch

+

15.6 inch

13.3 inch

2\*20 VFD



↙↘ 15.1 inch

or



↙↘ 15.1 inch

+

15.1 inch

2\*20 VFD



# Product Color



# Product Details





