

POS-G156 15.6 吋 windows 繁體中文 pos 15.1 吋 windows 繁體中文

(POS-G156/G151)

OCOM 的 pos 15.1 吋 windows 繁體中文 15.6 吋 windows 繁體中文 15.6 吋 windows 繁體中文 15.1 吋 windows 繁體中文 15.1 吋 windows 繁體中文 15.6 吋 windows 繁體中文 15.6 吋 windows 繁體中文...

□□

Intel Celeron 或 intel core I3 / I5
 支援 Msata SSD 64GB / SSD 128GB / 256 GB
 58mm / 80mm
 VFD 220
 MSR / VFD 220

□□

Model	POS-G156W/A	POS-G151W/A
Screen Size	15.6 吋 windows 繁體中文	15.1 吋 windows 繁體中文
Screen Resolution	1366*768	1024*768
Screen Brightness	250cd/m²	
Screen Aspect Ratio	16:10	
Screen Panel Type	GG	
Screen Connector	15.6 吋 windows 繁體中文 13.3 吋 windows 繁體中文 1366*768	15.1 吋 windows 繁體中文 1024*768
Screen Mounting	2*20 VFD 繁體中文	
OS		
windows J1900	CPU	Intel Celeron Bay Trail J1900 2.0GHz / intel core I3 / I5 4th CPU
	RAM	1*SO-DIMM DDRIII 1333*/1600 4GB 2GB/8GB
	Storage	Msata SSD 64GB 256GB
	Audio	Real Tek ALC662
	Network	10/100Mbs, Realtek RTL8111F Mini PCI-E WIFI
	Software	Windows 7/8/10, WEPOS, Linux
RK3288	CPU	Rockchip RK3288 / 1.8GHz RK3399
	RAM	DDRIII 2GB, 4GB
	ROM	16GB EMMC, 32GB
	Audio	Real Tek ALC5640
	Network	10/100Mbs, Realtek RTL8111F
	WIFI & BT	Wi-Fi 802.11b/g/n, BT 3.0/BT 4.0
OS	7.1	

Windows(J1900&RK3288)	12V DC *1 (RS232) * 1 RJ-45*1 USB*5 *1 , *1
Windows (J1900)	*1 VGA(15Pin D-sub)*1 RJ11 for Cash drawer *1 PS/2 *1
(RK3288)	RJ11 for Cash drawer *1 ,RJ11 from printer port for Cash drawer *1 TF*1
80mm	150mm/s 79.5-/ 0.5mm 72mm 100km USB
58mm	80mm/s 57.5-/ 0.5mm 48mm 50km LPT
MSR	MSR 15.6
	8Ohm/5W
	15.6Kg/6.5Kg/8.5Kg
	300*465*500mm
	0 40
	-10 60
	10%~80%
	10%~90%
	110-240V/50-60HZ ,DC12/5A 58mm DC12V/7A W/80mm
	FCC A /CE /LVD/CCC

All In One Touch Screen POS System

— .



Product Display

The whole machine featured anti-static protection, stronger EMI anti-interference, anti-ESD up to 8KV



Accessories



Thermal Printer



Barcode Scanner



Cash Drawer



Card Reader



Product
Accessories

SUPPORT SYSTEMS



WINDOWS



ANDROID



LINUX

Product Interface

Windows interfaces J1900



DC



LPT




COM



VGA



LAN



RJ11(optional)



USB 3.0*1



USB 2.0*4



PS/2



MIC-IN



LIN-OUT

Windows interfaces i3/i5



DC



HDMI



VGA



LAN



RJ11(optional)



USB 2.0*4



USB 3.0*1



MIC-IN



LIN-OUT

Android interfaces RK3288



DC



COM



LAN



RJ11(optional)*2



USB 3.0*1



USB 2.0*4



TF Card



MIC-IN



LIN-OUT

Screen Size



↙↘ 15.6 inch

or



↙↘ 15.6 inch

+

15.6 inch

13.3 inch

2*20 VFD



↙↘ 15.1 inch

or



↙↘ 15.1 inch

+

15.1 inch

2*20 VFD

Product Color



Product Details





