

# 15.6 15.1 POS POS

(M/N:POS-G156/G151)

OCOM Gpos... IO ...

I3 I5

Msata SSD 64GB SSD 128GB 256 GB

58mm 80mm

MSR VFD220

	POS-G156W/A	POS-G151W/A
	15.6 POS	15.1 POS
	15.6	15.1
	1366*768	1024*768
	250cd/m2	
	160*150	
	GG	
	15.6 13.3 1366*768	15.1 1024*768
	2*20 VFD	
J1900	Celeron Bay Trail J1900 2.0GHz intel core I3 / I5 4th CPU	
	1*SO-DIMM DDRIII 1333*/1600 4GB 2GB/8GB	
	Msata SSD 64GB 256GB	
	Real Tek ALC662	
	10/100Mbs, Realtek RTL8111F Mini PCI-E WIFI	
	Windows 7/8/10, POS, Linux	
RK3288	RK3288 1.8G RK3399	
	DDRIII 2GB 4GB	
	16GB EMMC 32GB	
	Real Tek ALC5640	
	10/100Mbs, Realtek RTL8111F	
	WIFI&BT Wi-Fi 802.11b/g/n, BT3.0/BT4.0	
	7.1	

Windows □ Android(J1900&RK3288)	□□ □□*1
	12V DC □□□□*1
	□□□RS232□* 1
	□□□□RJ-45*1
	USB *5
	□□□□*1 , □□□□*1
□□□J1900□	LPT *1
	VGA(15Pin D-sub)*1
	□□□ RJ11 *1□□□□
	PS/2 *1 □□□□□□
□□ (RK3288)	□□□ □□□RJ11*1□□□□□□□□□□RJ11*1□□□□
	TF□□*1
□□	
80mm□□□□□	□□□□□□
	150mm/s □□□□
	79.5-/ 0.5mm □□□□□□□□□□ 72mm
	□□□□□□□□□□□□□□100km
	USB □□
58mm□□□□□	□□□□□□
	80mm/s □□□□
	57.5-/ 0.5mm □□□□□□□□ 48mm
	□□□□□ 50km
	LPT □□
MSR	□□□ MSR □□□□ 15.6 □□
□□□□□	□□□□□□□□□□□□□□□□
□□□	□□ 80hm/5W □□□□□□□
□□	□□
□□	15.6□□□□6.5Kg□□□□8.5Kg
□□□□□□□	300*465*500mm
□□	
□□□□	0 □ 40 □□□
□□□□	-10 □ 60 □□□
□□□□	10%~80%
□□□□	10%~90%
□□	
□□□□□	110-240V/50-60HZ□□□□□□ ,DC12/5A □□□□□□ 58mm □□□□□□□□□□ DC12V/7A □□□□ W/80mm □□□□□□□□
□□□	□□□□□□□□□□/□□/□□□□□□□□
□□	□□□□□□□□□□□□
□□	
□□	FCC A □/CE □□/□□□□/CCC

# All In One Touch Screen POS System

---



# Product Display

The whole machine featured anti-static protection, stronger EMI anti-interference, anti-ESD up to 8KV



# Accessories



Thermal Printer



Barcode Scanner



Cash Drawer



Card Reader



Product  
**Accessories**

# SUPPORT SYSTEMS



WINDOWS



ANDROID




LINUX

# Product Interface


## Windows interfaces J1900




DC




LPT




COM



VGA



LAN



RJ11(optional)



USB 3.0\*1



USB 2.0\*4



PS/2



MIC-IN



LIN-OUT


## Windows interfaces i3/i5




DC




HDMI



VGA



LAN



RJ11(optional)



USB 2.0\*4



USB 3.0\*1



MIC-IN




LIN-OUT


## Android interfaces RK3288




DC



COM



LAN



RJ11(optional)\*2



USB 3.0\*1



USB 2.0\*4



TF Card



MIC-IN



LIN-OUT

# Screen Size



↙↘ 15.6 inch

or



↙↘ 15.6 inch

+

15.6 inch

13.3 inch

2\*20 VFD



↙↘ 15.1 inch

or



↙↘ 15.1 inch

+

15.1 inch

2\*20 VFD



# Product Color



# Product Details





