

# 15.6 15.1 POS

POS-G156 (G151)

OCOM Gpo...IO... ..

## 1. 2. 3. 4. 5. 6. 7. 8.

1. I3 I5
2. RK3288
3. EMMC 8/16GB/32GB
4. 64 GB ,SSd 128GB d 256 GB
5. 58mm 80mm
- 6.
7. MSR VFD220
- 8.

## Table

	POS-G156	POS-G151
	15.6 pos	15.1 pos
	15.6	15.1
	1366*768	1024*768
	25 0cd/2	
	1 60 ; 1 50	
	s	
	15.6 13.3 W / 1366*768	15.1 W / 1024*768
	2*20 VFD	
	Bay Trail J1900 2.0GHz I3 / I5 4 CPU	
	1*SO-DIMM DDRIII 1333*/1600 4GB 2GB/8GB	
	Msata SSD 64GB 256GB	
	Real Tek ALC662	
	10/100Mbps,Realtek RTL8111F	
	M PCI-E WIFI	
	2010 7 8 WEPOS, Linux	
	RK3568 , RK3 288, RK3399	
	DDRIV 2GB,4GB	
	16GB EMMC,32GB	
	RJ45 10/100Mbps	
	WIFI& 802.11b/g/n ,BT3.0/BT4.0	
	Android 7.1 Android 8.1 Android 11	

□□□□(J1900&RK3568)	p □ □□*1 12V DC □□*1 □□(RS232) * 1 □□□□RJ-45*1 USB * 5 M □□□□ in *1 , □□□□*1
□□ ( J1900)	□□*1 VGA(15Pin D-sub)*1 RJ11 □□□□ *1 □□□□□□ PS/2 *1 □□□□□□□□
□□ (RK3568)	□□□□ RJ11 □□□□ *1 ,RJ11 □□□□□□ □□□□*1□□□□□□ TF□□*1,SIM□□*1
□□	
80mm□□□□□□	□□□□□□ 150mm/s □□□□□□ 79.5-/ 0.5mm □□□□□□□□□□ 72mm □atuo□□□□□□□□□□100km USB□□
58mm□□□□□□	□□□□□□ 80mm/s □□□□□□ 57.5-/ 0.5mm □□□□□□□□□□ 48mm □□□□□□ 50km LPT□□
MSR	□□□□ MSR □□□□ 15.6 □□
□□□□□□	□□□□□□□□□□□□□□□□□□
□□□	□□ 80hm/5W □□□□□□□□
□□	
□□	□□ 6.5Kg , 15.6□□□□8.5Kg
□□□□□□	300*465*500mm
□□	
□□□□	0 □ 40 □□□□
□□□□	- 10 □ 60 □□□□
□□□□	10%~80%
□□□□	10%~90%
□□	
□□□□□□	110-240V/50-60HZ□□□□□□ i □□ , DC12/5A □□□□□□□□ 58mm □ □□□□□□□□□□ DC12V/7A □□ □□□□ □ W/80mm □□□□□□□□
□□□	□□□□□□□□□□□□□□□□□□□□□□
□□	□□□□□□□□□□□□□□□□□□
□□	
□□	FCC A □/CE □□/□□/□□□□

