

15.6 15.1 POS

POS-G156 (G151)

OCOM Gpo...IO... ..

1. 2. 3. 4. 5. 6. 7. 8.

1. I3 I5
2. RK3288
3. EMMC 8/16GB/32GB
4. 64 GB ,SSd 128GB d 256 GB
5. 58mm80mm
- 6.
7. MSR VFD220
- 8.

Table

POS-G156		POS-G151
15.6 pos		15.1 pos
...		
...		
15.6		15.1
1366*768		1024*768
25 0cd/2		
1 60 ; 1 50		
s		
15.6 13.3 W / 1366*768		151 W / 1024*768
2*20 VFD		
...		
CPU		Bay Trail J1900 2.0GHz I3 / I5 4 CPU
RAM		1*SO-DIMM DDRIII 1333*/1600 4GB 2GB/8GB
SSD		Msata SSD 64GB 256GB
Audio		Real Tek ALC662
Network		10/100Mbps,Realtek RTL8111F
Wireless		Mi PCI-E WIFI
OS		2010 7 8 WEPOS, Linux
Processor		RK3568 , RK3 288, RK3399
Memory		DDRIV 2GB,4GB
Storage		16GB EMMC,32GB
Network		RJ45 10/100Mbps
WIFI&BT		802.11b/g/n ,BT3.0/BT4.0
OS		Android 7.1 Android 8.1 Android 11
...		

□□□□(J1900&RK3568)	p □ □□*1 12V DC □□*1 □□(RS232) * 1 □□□□RJ-45*1 USB * 5 M □□□□ in *1 , □□□□*1
□□ (J1900)	□□*1 VGA(15Pin D-sub)*1 RJ11 □□□□ *1 □□□□□□ PS/2 *1 □□□□□□□□
□□ (RK3568)	□□□□ RJ11 □□□□ *1 ,RJ11 □□□□□□ □□□□*1□□□□□□ TF□□*1,SIM□□*1
□□	
80mm□□□□□□	□□□□□□ 150mm/s □□□□□□ 79.5- / 0.5mm □□□□□□□□□□ 72mm □atuo□□□□□□□□□□100km USB□□
58mm□□□□□□	□□□□□□ 80mm/s □□□□□□ 57.5- / 0.5mm □□□□□□□□□□ 48mm □□□□□□ 50km LPT□□
MSR	□□□□ MSR □□□□ 15.6 □□
□□□□□□	□□□□□□□□□□□□□□□□□□
□□□	□□ 80hm/5W □□□□□□□□
□□	
□□	□□ 6.5Kg , 15.6□□□□8.5Kg
□□□□□□	300*465*500mm
□□	
□□□□	0 □ 40 □□□□
□□□□	- 10 □ 60 □□□□
□□□□	10%~80%
□□□□	10%~90%
□□	
□□□□□□	110-240V/50-60HZ□□□□□□ i □□ , DC12/5A □□□□□□□□ 58mm □ □□□□□□□□□□ DC12V/7A □□ □□□□ □ W/80mm □□□□□□□□
□□□	□□□□□□□□□□□□□□□□□□□□
□□	□□□□□□□□□□□□□□□□□□
□□	
□□	FCC A □/CE □□/ LVD/CCC

