

(POS-H15) Pos Pos Pos Pos

M / N POS -H156W / A-H151W / A



OCOM H pos IO

- Intel Celeron i3 i5
- Rockchip RK3288
- EMMC 8GB / 16GB / 32GB
- MSATA SSD 64GB / SSD 128GB AN 256 GB
- 58mm / 80mm
- MSR VFD220
- / /

	POS -H156	POS -H151
	15.6 pos	15.1 pos
	15.6	15.1
	1366 * 768.	1024 * 768.
	250cd / m. ²	
	150; 140	
	G + G	

□□□	15.6 / 14/11.6□□□□□W / OR□W / O□□□□□□□□ □1366 * 768□□□	15.1□□□□□W / OR□W / O□□□□□□□□ □1024 * 768
□□□□	□□□2 * 20 VFD□□□□□	
□□		
Windows J1900.	□□	Intel Celeron Bay Trail J1900 2.0GHz□□□□□□□□□□I3 / I5 4□ CPU
	□□□□	1 * SO-DIMM DDRIII□□□□□1333 * / 1600 □□□ 2GB / 4GB / 8GB
	□□□□	MSATA SSD 64GB□HIGEL□□□□256GB
	□□	TEK ALC662□□□□
	□□	10 / 100MBS□Realtek RTL8111F LAN□□ □□□□PCI-E□□□□□□□□□□WiFi□□
	□□□□	Windows7 / 8/10□□□□□□POS□Linux
Android RK3288.	□□	Rockchip□□RK3288□Quad Core 1.8G□□□□RK3399
	□□□□	□DDRIII 2GB□□□□4GB
	□□□□	16GB emmc□□□□□32GB
	□□	TEK ALC5640□□□□
	□□	10 / 100MBS□Realtek RTL8111F LAN□□
	WiFi□BT□□	□□Wi-Fi 802.11b / g / n□bt3.0 / bt4.0□□
□□□□	Android 7.1.	
□□		
Windows / Android□J1900□RK3288□	□□□□* 1	
	12V□□□□□□□□	
	LAN□RJ-45 * 1	
	USB * 6.	
	mic in* 1□□□□out * 1	
Windows□J1900□	COM□RS232□* 1□□□□□HDMI * 1	
	VGA□15pin d-sub□* 1	
	□□□□□□□RJ11□* 1	
Android□RK3288□	COM□RS232□* 1	
	□□□□□□□RJ11□* 1□RJ11□□□□□□□□□□* 1□□□□	
	TF□□□* 1	
□□□		
80mm□□□□□□	□□□□□□□□	
	100mm / s	
	79.5 - / + 0.5mm□□□□□□□□□□72mm	
	□□□□□□□□□□50km	
	LPT□□	
58mm□□□□□□	□□□□□□□□	
	85□□/□	
	57.5 - / + 0.5mm□□□□□□□□□□48mm	
	□□□□□□50km	
	LPT□□	
MSR.	□□□MSR.	
□□□□□	□□□Web□□□□□□□□□□□□□□	
□□□	□□□□□1D□2D□□□□□	
□□□	□□□□□4□□/ 5W□□□□	
□□	□□	
□□	NET□5.6kg□□□□□7.7kg 15.6□15.6□□□□□□□□□□	
□□□□□□□□□□	340 * 450 * 480mm	
2IN1□□	700 * 460 * 500mm / gross□17kg	
□□		
□□□□	0□40□□□□	
□□□□	-10□60□□□□	
□□□□	10□□80□	
□□□□	10□□90□	

□□	
□□□□□	110-240V / 50-60Hz AC Power Input□□□W / 0□□□□DC12 / 5A□□□□□W / 58mm□□ □DC12V / 7A OUT□□□□W / 80MM□□□□□
□□□□	□□□□□□□□/□□/□□□□□□□□□□
CD□□□□	□□□□□□□□□□□□
□□	
□□	FCC□A / CE Mark / LVD / CCC

□□□□□

□□□□





POS-H15





POS-H15







POS-H15







POS-H15







POS-H15





POS-H15

