

POS1D 2D

M / NOCBS-W235



-
- 2.4G + USB
- 100
- 15000
-
-
- 600
-

	CMOS
	32
	1MP1280 * 800
	2.4G + USB2.4G + Bluetooth + USB
	2DPDF417Micro PDF 417QR CodeQR1 / 2MicroAztec
	1DUPC-AUPC-EEAN-8EAN-13Code128Code39Code 93Code32Code11CodabarPlesseyMSI2 of 5IATA 2 of 52 of 525PharmacodeRSS-14RSS-14RSS-14 LimitedCom pos ite Code-ACom pos ite Code-BCom pos ite Code-C

尺寸	1D≥400mm0.10mm
	2D≥700mm0.10mm
板厚	39-5mil60mm-120mm
	UPCA-13mil100mm35mm-310mm
板厚公差	±1/8mm
板厚公差	≥30°
板厚公差	±55°±55°
板厚	1500mAh20000mAh
板厚	5VDC±10%
板厚	±250mA±5%
板厚	0°C+ 50°C
板厚	-40°C+ 70°C
板厚	5%-95%



OCBS-W235





OCBS-W235





OCBS-W235





OCBS-W235





OCBS-W235





OCBS-W235



OCBS-W235

OCOM 1D 2D POS ID 500 1

OCOM DOT POS POS ISO CE FCC BIS

2007 6 OCOM ISO9001 2008 159 /
2300 50
O2 Equicom ...

OCOM " " ...

□OEM / ODM□

□□□□□□□□

► Company



► Certificates



► Payment



公司优势

·POS系统

·500强

·102 Star ...

·163 / 2600

·24

·12 OEM / ODM

·

·ISO 9001 FCC CE Rohs Soncap SASO POA BIS

·

·12 + 1

·“

·“



