

□□□ / O□(J1900/RK3288)	□□□□* 1
	100V-240V 50HZ/60HZ□□□□□□*1
	USB*2
	□□□□RJ-45*1
□□□□	
□□	□□□□617nm □□ LED
□□□□	5□□□
□□□□	UPC □ EAN □ Code128□Code 39□Code 93 □ Code 11□Interleaved 2 of 5□Matrix 2 of 5□Cod a bar□MSI Plessey□GS1 DataBar□□□□□□□□□□□□....
□□□□	PDF417□Micro PDF417□Data Matrix□Maxicode□QR Code□Micro QR□Aztec□Hanxin□.....
□□□□	4 □□□□ 39
□□□□□□	□□□ ±60°@ 0°Roll □ 0°Skew □□□± 360 ° @0 °□□□0 °□□ □□□± 65 ° @ 0 ° Roll □ 0 ° Pitch
□□□□	□□□
□□	USB
□□□	
80mm□□□□□□	□□□□
	1 5 0mm/s □□□□
	79.5-/+ 0.5mm □□□□□□□□□□ 72mm
	□□ □□□□
	□□ DC 24V
	□□□□203DPI
□□	
□□□□	0 □ 40 □□□
□□□□	- 10□60□□□□
□□□□	10%~80% □□□
□□□□	10%~90% □□□
□□	
□□□	□□□□/□□/□□□□□□□□□□□□□□□□
□□	□□□□□□□□□□□□□□□□
□□	
□□	FCC A □/CE □□/ LVD/CCC





