

□□□

□□□□□□□□□□□□□□□□
 21.5□1920*1080□□□□IPS□
 □□□□□□□□□□□□□□□□
 □□□□□□□□□□□□
 □□□□□□ □□
 □□□□□□□□□□
 □□□□□□□□□□□□□□□□□□□□□□□□
 □□80MM□□□□□□□□□□□□□□
 □□□□□□□□□□
 □□□□□□□□□□
 □□□□□□□□□□□□□□□□□□□□
 □□□□□□□□□□□□□□□□□□□□
 □□□□□□□□□□□□□□□□□□□□
 □□□□□□□□□□□□□□□□□□□□
 □□□□□□□□□□□□□□□□□□□□
 □□□□□□□□□□□□□□□□□□□□
 □□□□□□□□□□□□□□□□□□□□
 □□□□□□□□□□□□□□□□□□□□

□□□

□□	POS- K003 -W	POS- K003 -A
□□	21.5 □□□□□□□□□□□□□□□□	
□□	□□□□□□□□	
□□	□□□□□	
□□		
□□□□	21.5 □□□□□□□□□□	21.5 □□□□□□□□□□
□□□□	1920*1080	1920*1080
□□□□	25 0cd/□ ²	
□□	□□□□178□□□□178	
□□□□	10□ □□G+G □□□□	
□□		
□□	Intel Celeron Bay Trail J1900 2.0GHz □ intel core I3 / I5 □□ CPU □□	ARM Cortex-A17 -RK 3288 □□ 1.8GHz CPU
□□□□	1*SO-DIMM DDRIII□□□□ □□1333*/1600 4GB	□□ 2GB DDRIII
□□□□	Msata □□□□ 64GB	16GB eMMC
□□□□	□□Real Tek ALC662□□□□	□□Real Tek□□□□ □□ALC5640
□□□□	10/100Mbs□Realtek RTL8111F □□□□	10M/100M , RTL8201F
□□□□	□□ 802.11 a/b/g	□□ 802.11 a/b/g
□□□□	□□ 8 □□/10 □□□□	
□□	□□□□□□□□□□	
□□□□	Windows 7/8/10□ □□□□□□ □□POS, Linux	□□7.1
□□□□		

□□□ / O□(J1900/RK3288)	□□□□* 1
	100V-240V 50HZ/60HZ□□□□□□*1
	USB*2
	□□□□RJ-45*1
□□□□	
□□	□□□617nm □□ LED
□□□□	5□□□
□□□□	UPC □ EAN □ Code128□Code 39□Code 93 □ Code 11□Interleaved 2 of 5□Matrix 2 of 5□Cod a bar□MSI Plessey□GS1 DataBar□□□□□□□□□□□□....
□□□□	PDF417□Micro PDF417□Data Matrix□Maxicode□QR Code□Micro QR□Aztec□Hanxin□.....
□□□□	4 □□□□ 39
□□□□□	□□□ ±60°@ 0°Roll □ 0°Skew □□□± 360 ° @0 °□□□0 °□□ □□□± 65 ° @ 0 ° Roll □ 0 ° Pitch
□□□□	□□□
□□	USB
□□□	
80mm□□□□□	□□□□
	1 5 0mm/s □□□□
	79.5-/+ 0.5mm □□□□□□□□□□ 72mm
	□□ □□□□
	□□ DC 24V
	□□□203DPI
□□	
□□□□	0 □ 40 □□□
□□□□	- 10□60□□□
□□□□	10%~80% □□□
□□□□	10%~90% □□□
□□	
□□□	□□□□/□□/□□□□□□□□□□□□□□
□□	□□□□□□□□□□□□□□
□□	
□□	FCC A □/CE □□/ LVD/CCC





