## 

## 

OCOM POS-L156@pos@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@	

□□□□ Msata SSD 64GB□SSD 128GB □ 256 GB□□□□□

\_\_\_ MSR \_ VFD220 \_\_\_\_\_

	POS-L 156
	15.6000000POS00
	15.6
	1366 * 768
	2
	25 0cd / m
	15.6 W / DW/o1366*768
	2 * 20 VFD [[[]]]
	Intel Celeron Bay Trail J1900 2.0GHz , or intel celeron
	J4125, or intel core I3 / I 5 CPU □□
	1 * SO-DIMM DDRIII 4GB DDR3L / 1333 MHZ 8GB
	Msata SSD 64GB DDDDD 256GB
	□□Real Tek ALC662□□□□
	10 / 100Mbs, Realtek RTL8111F □□
	Windows 7/8/10
000	

Laga	GDD44
I /O□ J1900	□□12V DC * 1
	LAN_RJ-45*1RJ11
	USB * 6
	15PIN D-sub VGA * 1
	RS 232 * 1
80mm[][][]	
	1 5 0mm/s [[[[[
	79.5 - / + 0.5mm   72mm   72mm
	00000000000 50km
58mm[][][]	
	85mm/s [[[[[
	57.5 - / + 0.5mm   48mm
	□□□□ 50km
MSR	□□□ MSR
	□□ 4ohm / 5w □□□□□□□
	□□□6.5 Kg □□ □□□8.0 Kg for 15.6 with1 5 .6 dual screen with
	built-in Printer
	490 * 31 0 * 48 5
	110-240V / 50-60HZ [[[[[]]]]]DC12 / 5A[[[]][[[]]]] W / o [[[]]]
	□ W / 58mm □□□ DC12V / 7A□□ □□□□□□□ W / 80mm □□□

































