

# (POS-L156) Windows Pos I3

## POS-L156

OCOM POS-L156 pos IO

□□

□□□□□□□□□□ I3 I5 □□□□□□□□  
 □□□□ Msata SSD 64GB □ SSD 128GB □ 256 GB □□□□□  
 58mm □ 80mm □□□□□□□□□□  
 □□□□□□□□□□  
 □□□□ MSR □ VFD220 □□□□□□□□□□  
 □□□□□□□□□□

□□

□□	POS-L 156
□□	15.6□□□□□□□□ POS□□
□□	□□□□□□□
□□	□□□□□□□ □□
□□	15.6□□□□□□□□
□□	1366 * 768
□□	25 0cd / m <sup>2</sup>
□□□□	□□□□1 60 □□□□1 50
□□	□□ □□G+G □□□□
□□	15.6□□□□ W / □W/o□□□□□□□□1366*768□□
□□	2 * 20 VFD □□□□□□□□□□
□□	Intel Celeron Bay Trail J1900 2.0GHz , or intel celeron J4125, or intel core i3 / i5 CPU □□
□□□□	1 * SO-DIMM DDRIII□□□□□□ 4GB DDR3L / 1333 MHZ□□□□□ 8GB □□
□□□□	Msata SSD 64GB □□□□□□□ 256GB
□□	□□Real Tek ALC662□□□□□
□□	10 / 100Mbs, Realtek RTL8111F □□ □□Mini PCI-E□□□□□□□□□□WIFI□□
□□□□	Windows 7/8/10 □□□□□□□□□□WEPOS□□Linux
□□	

8000 I/O J1900	8000*1
	12V DC * 1
	LAN RJ-45*1 RJ11
	USB * 6
	15PIN D-sub VGA * 1
	RS 232 * 1
	8000*1 MIC*1
80mm	8000
58mm	85mm/s
	79.5 - / + 0.5mm 72mm
	50km
	85mm/s
MSR	MSR
	4ohm / 5w
	6.5 Kg 8.0 Kg for 15.6 with 15.6 dual screen with built-in Printer
	490 * 310 * 48.5
	110-240V / 50-60HZ DC12 / 5A W / o W / 58mm DC12V / 7A W / 80mm

8000

















